## WYOMING GAME AND FISH DEPARTMENT

#### FISH DIVISION

## ADMINISTRATIVE REPORT

TITLE: Instream Flow Studies on Poker Hollow Creek, a Bonneville Cutthroat Trout (Oncorhynchus clarki utah) Stream.

PROJECT: IF-PE97-07-9701

AUTHOR: Paul D. Dey and Thomas C. Annear

DATE: March 1997

## ABSTRACT

Studies were conducted in 1996 on Poker Hollow Creek to determine instream flows necessary for maintaining Bonneville cutthroat trout (BRC) habitat and populations. Studies complemented ongoing population and habitat monitoring of BRC streams (Remmick et al. 1994).

Physical Habitat Simulation (PHABSIM), the Habitat Quality Index (HQI), and the Habitat Retention Method were used to derive instream flow water right recommendations. Recommendations are: October 1 - May 31 = 3.7 cfs, June 1 - June 30 = 42 cfs, and July 1 - September 30 = 3.7 cfs.

## INTRODUCTION

Wyoming Bonneville cutthroat trout (*Oncorhynchus clarki utah*) populations occur primarily in the Thomas Fork and Smiths Fork watersheds. These major Bear River tributaries and associated waterways were surveyed for physical, chemical, and biological characteristics between 1966 and 1977 (Miller 1977). Binns (1981) reviewed the distribution, genetic purity, and habitat conditions for Bonneville cutthroat trout populations. Recent population and habitat survey results are in Remmick (1981, 1987) and Remmick et al. (1994).

In general, populations are limited by seasonally low flows, lack of riparian cover, thermal pollution arising in conjunction with low flows and reduced riparian vegetation, and silt pollution (Binns 1981). Livestock grazing on both private and public lands is an important contributor to degraded habitat conditions. However, despite habitat challenges, significant populations remain throughout the native range and a recent review categorized Wyoming's populations as "95% secure, stable" (Duff 1996). Population status in other Bonneville basin states including Utah, Idaho and Nevada is less secure. Therefore, Bonneville cutthroat trout were recently petitioned for listing under the Endangered Species Act but are not listed at this time. Status review was initiated in response to concerns expressed by the Idaho Fish and Game Department, the Desert Fishes Council and the Utah Wilderness Association. This species is considered "rare" by the Wyoming Game and Fish Department (WGFD 1977).

A 5-year management plan for Wyoming, developed by the Wyoming Game and Fish Department (WGFD) in coordination with the U.S. Forest Service (USFS) and U.S. Bureau of Land Management (BLM), outlines management goals and provides criteria for listing Bonneville cutthroat trout as threatened (Remmick et al. 1994). The plan's purpose is to outline management practices to prevent listing by moving toward wider distribution and higher populations. The plan recommends that status decisions be made after five-years of population and habitat monitoring. Habitat protection by acquiring instream flow water rights will help prevent additional population declines.

Resource management practices could be significantly affected by listing Bonneville cutthroat trout as Threatened or Endangered. Instream flow water right identification and acquisition on Bonneville cutthroat trout streams is important to help avoid listing. Therefore, since 1993 the WGFD has filed for instream flow water rights on most non-ephemeral tributaries with documented BRC presence in the Thomas and Smiths Fork drainages. Studies in 1996 focused on Poker Hollow Creek, Lander Creek, North Fork Smiths Fork Creek, Trespass Creek, Packstring Creek, and Little White Creek.

Study objectives were to 1) investigate the relationship between discharge and physical habitat quantity and quality for Bonneville cutthroat trout and, 2) determine an instream flow regime necessary to maintain or improve Bonneville cutthroat trout populations.

## METHODS

## Study Area

Poker Hollow Creek is a tributary to the Smiths Fork River (Figure 1). The Poker Hollow Creek basin is managed by the Bridger-Teton National Forest for multiple use including livestock grazing and oil and gas drilling. The valley has a southerly aspect with fairly steep sides. Coniferous communities predominate at higher elevations while aspens occur sporadically and in hillside valleys. Riparian vegetation consists of willow, grass and forbs. Stream gradient estimated from a USGS 7.5 minute quadrangle map is between 2.5 and 3.8% and the channel type was rated as B2 (Rosgen 1985). This rating indicates a moderately entrenched channel that is well confined by its valley and has bed material composed of large cobble, course gravel and sand.

Though riparian and upland conditions are fairly pristine, several factors naturally limit BRC populations. Average basin elevation at 2429 meters above mean sea level is among the highest occurring in BRC's natural range. Summers and corresponding growing seasons are short at higher elevations. Fairly high channel gradient results in fewer pools, higher water velocities and hence fewer low velocity shelter areas.



Figure 1. Poker Hollow Creek Instream Flow Segment No.

#### Fisheries

The term "fishery" refers to fish populations and their associated habitat in a defined area. Instream flow water rights are intended to maintain or improve habitat conditions so that viable fisheries are maintained or improved. Trout populations, particularly in small mountain streams, normally fluctuate widely. In a western Oregon stream studied for 11 years, density of age 0 cutthroat trout (fry, <2 inches) varied from 8 to 38 per 100 m<sup>2</sup> and density of age 1 cutthroat trout (juveniles, 4-4.5 inches) ranged from 16 to 34 per 100 m<sup>2</sup> (House 1995). In this example, population fluctuations occurred despite the fact that habitat conditions were not degraded and appeared to be relatively stable. The author suggested that small changes in peak winter flows between years would have accounted for shifts in overwinter survival between age-classes.

Similar population fluctuations occur in Sand Creek, a Crook County, Wyoming stream that experiences relatively little discharge variation (Mueller 1987). Sand Creek brown trout population density ranged from 646 trout/mile to 4,060 trout/mile in a three year period. Biomass estimates for the same period ranged between 48 and 142 pounds per acre.

Long-term trout population maintenance in small streams depends on periodic strong year classes produced in good flow years. Without benefit of periodic favorable flows, populations in some streams would decline or disappear. The WGFD instream flow strategy recognizes the inherent variability of trout populations and thus defines the "existing fishery" as a dynamic feature. Instream flow recommendations are based on a goal of maintaining habitat conditions that provide the opportunity for trout numbers to fluctuate within existing natural levels.

Population data collected in 1981 near the mouth of Poker Hollow Creek indicate 45 BRC/mile with a standing crop of 2.4 pounds BRC/acre (Remmick 1981). In addition, brook trout were found in approximately equal abundance. On August 26, 1996 a 508 foot station yielded 5 BRC ranging in length from 3.6 to 12.1 inches. The corresponding population estimate of 54 BRC/mile is similar to that measured in 1981. Although no brook trout were collected in 1996, a single brown trout was sampled.

## Habitat Modeling

After visually surveying approximately two stream miles on June 4, a study site was located at Township 29N, Range 117W, Section 4, NE1/4. (Figures 1-3). The representative site contained trout cover associated mostly with lateral scour pools and pocket water. Infrequent overhead cover is provided by willows and undercut banks. Eight transects were distributed among pool, run, and riffle habitat types (Appendix 1).

Instream flow filing recommendations derived from this site were applied to a 1.6 mile-long reach extending downstream from the confluence of two unnamed forks at T30N, R117W, S4 to the confluence with Smiths Fork River at T29N, R117W, S9. The land through which the proposed segment passes is under Bridger-Teton National Forest administration.

Data for calibrating simulations were collected between June 25 and September 7, 1996. Collection dates and corresponding discharges are listed in Table 1. Additional flow measurements of 76 and 6.2 cfs were made on June 4 and August 26, respectively.



Lower end study site

Table 1. Dates and discharges Poker Hollow Creek instream flow data were collected in 1996.

Date	Discharge (cfs)
June 25	53
July 10	20
September 7	3.7

Determining critical trout life stages (fry, juvenile, adult, etc.) for a particular time period aids in focusing flow recommendations. Critical life stages are those most sensitive to environmental stresses. Annual population integrity is sustained by providing adequate flow for critical life stages. In many cases, trout populations are constrained by spawning and young (fry and juvenile) life stage habitat "bottlenecks" (Nehring and Anderson 1993). Therefore, our general approach includes ensuring that adequate flows are provided to maintain spawning habitat in the spring was well as juvenile and adult habitat throughout the year (Table 2).

Table 2. Bonneville cutthroat trout life stages and months considered in Poker Hollow Creek instream flow recommendations. Numbers indicate method used to determine flow requirements.

Life Stage	Jan	Feb	Mar	Apr	Мау	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Adult							1	1	1			
Spawning						2						
All	3	3	3	3	3	3	3	3	3	3	3	3
1 - Habitat Ou	allitur 1	Indox										

1 - Habitat Quality Index

2 - PHABSIM

3 - Habitat Retention

## Habitat Retention Method

A Habitat Retention method (Nehring 1979, Annear and Conder 1984) was used to identify a maintenance flow by analyzing data from three hydraulic control riffle transects. A maintenance flow is defined as the continuous flow required to maintain specific hydraulic criteria in stream riffles. Year-round criteria maintenance in riffles ensures that habitat is also maintained in other habitat types such as runs or pools (Nehring 1979). In addition, maintenance of identified flow levels may ensure passage between habitat types for all trout life stages and maintain adequate benthic invertebrate survival.

A maintenance flow is realized at the discharge for which any two of the three criteria in Table 3 are met for all riffle transects in a study area. The instream flow recommendations from the Habitat Retention method are applicable year round except when higher instream flows are required to meet other fishery management purposes (Table 2).

Table 3. Hydraulic criteria for determining maintenance flow with the Habitat Retention method.

Category	Criteria
Mean Depth (ft)	Top Width <sup>a</sup> X 0.01
Mean Velocity (ft/s)	1.00
Wetted Perimeter (%) <sup>b</sup>	50
a At average detile fleet on mean	death 0.00 list

a - At average daily flow or mean depth = 0.20, whichever is greater
b - Percent of bank full wetted perimeter

Simulation tools and calibration techniques outlined below for hydraulic simulation in PHABSIM are also used with this technique. The major difference with this technique is that only hydraulic control riffles are examined and no direct reference is made to suitability of identified depths and velocities for trout life stages. Instead, the AVDEPTH model under PHABSIM is used to simulate average cross section depth, wetted perimeter and velocity for a range of flows on each cross section. The flow that maintains 2 out of 3 criteria for all three transects is then readily apparent.

## Habitat Quality Index

The Habitat Quality Index (HQI; Binns and Eiserman 1979, Binns 1982) was used to estimate trout production over a range of late summer flow conditions. This model was developed by the WGFD and received extensive testing and refinement. It has been reliably used in Wyoming for trout standing stock gain or loss assessment associated with instream flow regime changes. The HQI model includes nine attributes addressing biological, chemical, and physical aspects of trout habitat. Results are expressed in trout Habitat Units (HUs), where one HU is defined as the amount of habitat quality that will support about 1 pound of trout. HQI results were used to identify the flow needed to maintain existing levels of Bonneville cutthroat trout production between July 1 and September 30 (Table 2).

In the HQI analysis, habitat attributes measured at various flow events are assumed to be typical of mean late summer flow conditions. For example, stream widths measured in June under high flow conditions are considered a fair estimate of the stream width that would occur if the same flow level occurred in the month of September. Under this assumption, HU estimates are extrapolated through a range of potential late summer flows (Conder and Annear 1987). Poker Hollow Creek habitat attributes were measured on the same dates PHABSIM data were collected (Table 1). Some attributes were mathematically derived to establish the relationship between discharge and trout production at discharges other than those measured.

Average daily flow (ADF;6.4 cfs) and peak flow (87 cfs) estimates for determining critical period stream flow and annual stream flow variation are based on elevation and basin area (Lowham 1988). Although some variation exists around these flow estimates, the fact that a dimension-less index (Habitat Units) is produced from combining attributes suggests that this variation can be ignored. A Ryan temperature recorder monitored water temperature at 4 hour intervals between June 25 and September 7.

#### Physical Habitat Simulation

Physical Habitat Simulation (PHABSIM) methodology was used to quantify physical habitat (depth and velocity) availability for life stages over a range of discharges. The methodology was developed by the Instream Flow Service Group of the U.S. Fish and Wildlife Service (Bovee and Milhous 1978) and is widely used for assessing instream flow relationships between fish and physical habitat (Reiser et al. 1989).

The PHABSIM method uses empirical relationships between physical variables (depth, velocity, and substrate) and suitability for fish to derive weighted usable area (WUA; suitable ft<sup>2</sup> per 1000 ft of stream length) at various flows. Depth, velocity, and substrate were measured along transects (*sensu* Bovee and Milhous 1978) on the dates in Table 1. Hydraulic calibration techniques and modeling options in Milhous et al. (1984) and Milhous et al. (1989) were employed to incrementally estimate physical habitat between 1 and 100 cfs. Precision declines outside this range; however, the modeled range accommodates typical Poker Hollow Creek flows.

Curves describing depth, velocity and substrate suitability for trout life stages are an important component of the PHAMSIM modeling process. Suitability curves used for deriving recommendations are listed in Appendix 2.

Binns (1981) estimated that peak Bonneville cutthroat trout spawning occurs during periods of maximum run-off and average water temperatures between 45° and 48° F. These conditions are most likely to occur during June in Poker Hollow Creek (stream elevation 7880-8200+ feet; mean basin elevation = 9000). Because spawning onset and duration varies between years due to differences in flow quantity and water temperature, spawning recommendations should extend from June 1 to June 30. Even if spawning is completed before the end of this period, maintaining flows at a selected level throughout June will benefit trout egg incubation by preventing dewatering. The PHABSIM model was used in making flow recommendations for maintaining BRC spawning habitat from June 1 to June 30 (Table 2).

The time periods selected for spawning flow recommendations differ among streams. Because it is the highest elevation stream examined, Poker Hollow Creek's spawning flow recommendation is for June only. On North Fork Smiths Fork, the lower elevation means that spawning may begin in late May hence the recommended May 15 to June 30 period. Spawning recommendations for many BRC streams cover the entire May through June period. The lowest elevation streams (Huff Ck., Howland Creek, Salt Creek) have spawning recommendations applied from April 15 through June 30.

## RESULTS AND DISCUSSION

# Habitat Retention Analysis

Habitat retention analysis indicates that 3.7 cfs is required to maintain hydraulic criteria at all riffles (Table 4). Maintenance of naturally occurring flows up to this flow is necessary at all times of the year. However, results from the HQI and PHABSIM methods may indicate that higher flows are needed during June through September to support spawning and adult life stages (below, Table 2).

Table 4. Simulated hydraulic criteria for three Poker Hollow Creek riffles Average daily flow = 6.4 cfs. Bank full discharge = 41 cfs.

Mean	Mean	Wetted	
Depth	Velocity	Perimeter	Discharge
(ft)	(ft/s)	(ft)	(cfa)
Riffle 1 0.82	4.12	30.8	100
0.71	2.83	21.3	41
0.40	1.51	17.1	10
0.38	1.32	14.6	7.0
0.39	1.07	10.7 <sup>ª</sup>	43
0.39	1.03	10.2	4.0
0.39	1.00*	9.9	3.7 <sup>b</sup>
0.37	0.89	9.5	3.0
0.31	0.73	9.1	2.0
0.25	0.53	7.8	1.0
<0.25	<0.53	<7.8	<1.0
iffle 2 0.99	5.40	19.7	100
0.94	3.35	13.8	41
0.72	2.26	12.9	20
0.55	1.60	11.8	10
0.48	1.35	11.3	7.0
0.41	1.16	10.9	5.0
0.37	1.06	10.6	4.0
0.35	1.00	10.4	3.5
0.28	0.82	9.0	2.0
0.23	0.65	7.0	1.0 <sup>b</sup>
<0.23*	<0.65	<7.0	<1.0
iffle 3 1.13	5.00	18.8	100
0.87	3.13	16.0	41
0.55	1.52	12.7	10
0.53	1.26	11.0	7.0
0.48	1.06	10.4	5.0
0.47	1.00*	10.2	4.5
0.43	0.87	9.7	3.5
0.38	0.65	8.5	2.0
0.28	0.45	8.1*	1.0 <sup>b</sup>
<0.28	<0.45	<8.1	<1.0

a - Hydraulic criteria met

b - Discharge at which 2 of 3 hydraulic criteria are met

Trout populations are naturally limited by extreme conditions during the winter months (October through March; Needham et al. 1945, Reimers 1957, Butler 1979, Kurtz 1980, Cunjak 1988, Cunjak 1996). Formation of frazil ice (suspended ice crystals formed from super-chilled water) in high gradient stream reaches can be both a direct mortality source through gill abrasion and subsequent suffocation or an indirect mortality source as resultant anchor ice limits habitat, causes localized de-watering, and extracts excessive metabolic demands on fish forced to seek ice-free habitats (Brown et. al 1994). Pools downstream from high gradient frazil ice-forming areas can accumulate anchor ice when woody debris or surface ice provides anchor points for frazil crystals (Brown et. al 1994, Cunjak and Caissie 1994). Such accumulations may result in mortalities if emigration is blocked by low winter flows or ice dams.

In high gradient systems, groundwater influx areas, ice covered pools not close to frazil sources, heavy snow cover with stream bridging, and pools with little woody debris offer refugia from frazil ice (Brown et al. 1994). Lower gradient streams and narrow streams are more likely to have insulating surface ice cover or at higher elevations, heavy snow cover and bridging. Poker Hollow Creek's high elevation, relatively narrow width and moderate slope likely means that heavy snow fall will result in snow bridging. Frazil ice formation is likely a concern mainly in early winter before sufficient insulating snow is present or in late winter when snow melt becomes superchilled by flowing over snow and ice before entering the stream. Therefore, natural winter flow levels up to the identified 3.7 cfs should be maintained to maximize access to and availability of frazil-ice-free refugia. Any artificial reduction of natural winter stream flows could increase trout mortality and effectively reduce the number of fish the stream could support.

The 3.7 cfs identified by the Habitat Retention Method may not always be present during the winter. Because the existing fishery is adapted to natural flow patterns, occasional shortfalls during the winter do not imply a need for additional storage. Instead, they illustrate the necessity of maintaining all natural winter stream flows, up to 3.7 cfs, to maintain existing trout survival rates.

## Habitat Unit Analysis

Article 10, Section d of the Instream Flow Act states that waters used for providing instream flows "shall be the minimum flow necessary to maintain or improve existing fisheries". Often, HU's measured during low flow are used to define the existing late summer fisheries. In situations where the goal is to "maintain" existing fisheries, we determine the flow range with the same HU's as measured and the minimum flow in that range becomes the recommendation. At the measured late summer flow of 3.7 cfs, HQI analysis indicates approximately 57 trout HUs (Figure 4). This level of habitat is maintained between flows of 3.5 and 5.9 cfs. However, 3.5 cfs is below the year-round maintenance flow of 3.7 cfs determined above with the habitat retention method. Therefore, the minimum flow to maintain the fishery during late summer is 3.7 cfs.





Habitat units are maximized between average late summer discharges of 6.0 and 14 cfs. Based on HQI analysis and in consideration of Management Plan goals (Remmick et al. 1994), an instream flow of 3.7 cfs is recommended to maintain existing trout production between July 1 and September 30. This flow represents the lowest stream flow that will accomplish this objective. Storage to achieve this flow more frequently than naturally available is not needed to maintain the existing fishery.

## PHABSIM Analyses

Weighted usable area estimates for Bonneville cutthroat trout life stages are illustrated in Figure 5. Bi-modal peaks for adult and juvenile physical habitat occur at about 3.5 and 3.0 cfs and again at 38 and 40 cfs, respectively. The peaks at 3.0 - 3.5 cfs occur because favorable velocities are available in pools of adequate depth. Lower flow levels result in decreases in areas with adequate depth. Flow levels between the two peaks result in physical habitat decreases because velocities are generally high. The second peak at 38 - 40 cfs occurs as bank-side habitat is inundated providing adequate depth and slower velocities. Normal latesummer habitat levels occur at flow levels near the 3.5 cfs peak for adults. Therefore, the recommended late-summer flow of 3.7 cfs from habitat retention would maintain adequate adult and juvenile physical habitat.

Spawning was identified as a critical life stage. Peak spawning physical habitat occurs at 42 cfs. Normal spring flows are much higher - 76 cfs was measured on June 4, 1996. Such high flows might limit spawning activity near the study site and trout probably migrate to more favorable reaches or smaller tributaries. Though trout can usually find spawning habitat whenever temperatures are appropriate and flows allow unrestricted movement, maximum physical habitat in the study site occurs at a flow of 42 cfs. Therefore, an instream flow of 42 cfs is recommended for the period June 1 to June 30.



Figure 5. Weighted usable area (percent of maximum) for Bonneville cutthroat trout in Poker Hollow Creek over a range of discharges. X-axis discharges are not to scale.

#### INSTREAM FLOW RECOMMENDATIONS

Based on the analyses and results outlined above, the instream flow recommendations in Table 5 will maintain the existing Poker Hollow Creek Bonneville cutthroat trout fishery. These recommendations apply to a 1.6 mile Poker Hollow Creek segment extending downstream from the confluence of two unnamed forks at T30N R117W, S4 to the confluence with Smiths Fork River at T29N, R117W, S9. The land through which the proposed segment passes is under Bridger-Teton National Forest administration. Because data were collected from representative habitats and simulated over a wide flow range, additional data collection under different flow conditions would not significantly change these recommendations.

Table 5. Instream flow recommendations to maintain the existing Poker Hollow Creek trout fishery.

Time	Instream Flow Recommendation (cfs)		
Period			
June 1 to June 30	42		
July 1 to May 31	3.7		

This analysis does not consider periodic requirements for channel maintenance flows. Because this stream is unregulated, channel maintenance flow needs are adequately met by natural runoff patterns. If regulated in the future, additional studies and recommendations may be appropriate for establishing channel maintenance flow requirements.

- Annear, T.C. and A.L. Conder. 1984. Relative bias of several fisheries instream flow methods. North American Journal of Fisheries Management 4:531-539.
- Binns, N.A. 1982. Habitat Quality Index Procedures Manual WDFG Publication
- Binns, N.A. 1981. Bonneville cutthroat trout Salmo clarki utah in Wyoming Wyoming Game and Fish Department, Fisheries Technical Bulletin No. 5.
- Binns, N.A. and F. Eiserman. 1979. Quantification of fluvial trout habitat in Wyoming. Transactions of the American Fisheries Society 108:215-228.
- Bovee, K. and R. Milhous. 1978. Hydraulic simulation in instream flow studies: theory and technique. Instream Flow Information Paper 5, FWS/OBS-78/33, Cooperative Instream Flow Service Group, U.S. Fish and Wildlife Service. Fort Collins, Colorado.
- Bozek, M.A. and F.J. Rahel. 1992. Generality of microhabitat suitability models of young Colorado River cutthroat trout (*Oncorhynchus clarki pleuriticus*) across site and among years in Wyoming streams. Canadian Journal of Fisheries and Aquatic Science 49:552-564.
- Brown, R.S., S.S. Stanislawski, and W.C. Mackay. 1994. Effects of frazil ice on fish. In Proceedings of the Workshop on the Environmental Aspects of River Ice, Saskatoon, Sask., 18-20 August 1993. Edited by T.D. Prowse. NHRI Symp. Ser. No.12. National Hydrology Research Institute, Saskatoon, Sask. pp.261-278.
- Butler, R. 1979. Anchor ice, its formation and effects on aquatic life Science in Agriculture, Vol XXVI, Number 2, Winter, 1979.
- Conder, A.L. and T.C. Annear. 1987. Test of weighted usable area estimates derived from a PHABSIM model for instream flow studies on trout streams. North American Journal of Fisheries Management 7:339-350.
- Cunjak, R.A. 1988. Physiological consequences of overwintering in streams; the cost of acclimatization? Canadian Journal of Fisheries and Aquatic Sciences 45:443-452.
- Cunjak, R.A. 1996. Winter habitat of selected stream fishes and potential impacts from land-use activity. Canadian Journal of fisheries and Aquatic Sciences 53 (Suppl.1):267-282.
- Cunjak, R.A. and D. Caissie. 1994. Frazil ice accumulation in a large salmon pool in the Miramichi River, New Brunswick: ecological implications for overwintering fishes. In Proceedings of the Workshop on the Environmental Aspects of River Ice, Saskatoon, Sask., 18-20 August 1993. Edited by T.D. Prowse. NHRI Symp. Ser. No.12. National Hydrology Research Institute, Saskatoon, Sask. pp.261-278.
- Duff, Donald. 1996. Conservation assessment for inland cutthroat trout. U.S. Department of Agriculture, Forest Service, Intermountain Region, Ogden, Utah Pages 35-73.

- House, R. 1995. Temporal variation in abundance of an isolated population of cutthroat trout in western Oregon, 1981-1991. North American Journal of Fisheries Management 15:33-41.
- Kurtz, J. 1980. Fishery management investigations. a study of the upper Green River fishery, Sublette County, Wyoming (1975-1979). Completion Report. Wyoming Game and Fish Department, Fish Division, Cheyenne.
- Lowham, H.W. 1988. Streamflows in Wyoming. USGS Water Resources Investigations Report 88-4045.
- Milhous, R.T., D.L. Wegner, and T. Waddle. 1984. User's guide to the physical habitat simulation system. Instream Flow Paper 11, FWS/OBS-81/43, U.S. Fish and Wildlife Service, Fort Collins, Colorado.
- Milhous, R.T., M.A. Updike, and D.M. Schneider. 1989. Physical habitat simulation system reference manual - version II. Instream Flow Information Paper No. 26. U.S. Fish and Wildlife Service, Biol. Rep. 89(16).
- Miller, D.D. 1977. Comprehensive survey of the Bear River drainage. Wyoming Game and Fish, Administrative Report.
- Mueller, J.W. 1987. Electrofishing results in Sand Creek, Hospital Gulch Station, Sand Creek Country Club, 1986. Wyoming Game and Fish Department Administrative Report.
- Needham, P., J. Moffett, and D. Slater. 1945. Fluctuations in wild brown trout populations in Convict Creek, California. Journal of Wildlife Management 9:9-25.
- Nehring, R. 1979. Evaluation of instream flow methods and determination of water quantity needs for streams in the state of Colorado. Colorado Division of Wildlife, Fort Collins.
- Nehring, B.R. and R.M. Anderson. 1993. Determination of population-limiting critical salmonid habitats in Colorado streams using the Physical Habitat Simulation System. Rivers 4:1-19.
- Reimers, N. 1957. Some aspects of the relation between stream foods and trout survival. California Fish and Game 43:43-69.
- Reiser, D.W., T.A. Wesche, and C. Estes. 1989. Status of instream flow legislation and practices in North America. Fisheries 14(2):22-29.
- Remmick, R. 1981. A survey of native cutthroat populations and associated stream habitats in the Bridger-Teton National Forest. Wyoming Game and Fish Department, Administrative Report.
- Remmick, R. and N.A. Binns. 1987. Effect of drainage wide habitat management on Bear River cutthroat trout (Salmo clarki utah) populations in the Thomas Fork drainage, Wyoming. Wyoming Game and Fish Department, Administrative Report.
- Remmick, R., K. Nelson, G. Walker, and J. Henderson. 1994. Bonneville cutthroat trout inter-agency five year management plan (1993-1997).

Rosgen, D. 1985. A stream classification system. IN: Riparian Ecosystems and Their Management; Reconciling Conflicting Uses. Proceedings of the First North American Riparian Conference, April 16-18, Tucson, Arizona. GTR-RM120, pp. 91-95.

WGFD. 1977 Current Status and Inventory of Wildlife in Wyoming. 133 p.

Transect	Length (ft)	Weight	Percent	Habitat Type
0.0	9.8	1.00	26	Riffle/Control/IFG1
19.5	13.0	0.50	35	Run
26.0	9.0	0.50	24	Run/Pool
37.5	5.7	0.50	15	Pool
	5.5	0.50	29	Riffle/Control/IEG1
11.0	8.7	0.40	46	Run
19.0	4.8	0.00	25	Pool
	NA	NA	NA	Stand-alone Riffle/Control/IFG1

Appendix 1. Reach weighting used for PHABSIM Analysis

Appendix 2. Spawning suitability index data used in PHABSIM analysis. Index data were developed by WGFD from 1994 observations in Huff Creek.

Spawning	Velpcity	Weight	Depth	Weight	Substrate	Weight
		0.00	A 4 5	0.00	A A A	
		0.00		0.03		
		0.01		0.08		
		0.02		0.15		
		0.03		0.30		
		0.06		0.51		
		0.11		0.70		
		0.19		0.90		
		0.25		1.00		
		0.32		1.00		
		0.44		0.82		
		0.54		0.64		
		0.64		0.41		
		0.74		0.23		
		0.83		0.12		
		0.93		0.05		
		0.98		0.01		
		1.00		0.00		
		1.00		0.00		
		0.96				
		0.91				
		0.80				
		0.71				
		0.60				
		0.47				
		0.38				
		0.00				
		0.00				