NUMERICAL MODELLING OF MULTIPHASE FLOW IN POROUS MEDIA

Myron B. Allen III

December 1985

Journal Article

WWRC-85-37

In

Adv. Water Resources

Volume 8

Myron B. Allen III Department of Mathematics University of Wyoming Laramie, Wyoming

Numerical modelling of multiphase flow in porous media

Myron B. Allen III

Department of Mathematics, University of Wyoming, Laramie, Wyoming 82071, USA

The simultaneous flow of immiscible fluids in porous media occurs in a wide variety of applications. The equations governing these flows are inherently nonlinear, and the geometries and material properties characterizing many problems in petroleum and groundwater engineering can be quite irregular. As a result, numerical simulation often offers the only viable approach to the mathematical modelling of multiphase flows. This paper provides an overview of the types of models that are used in this field and highlights some of the numerical techniques that have appeared recently. The exposition includes discussions of multiphase, multispecies flows in which chemical transport and interphase mass transfers play important roles. The paper also examines some of the outstanding physical and mathematical problems in multiphase flow simulation. The scope of the paper is limited to isothermal flows in natural porous media; however, many of the special techniques and difficulties discussed also arise in artificial porous media and multiphase flows with thermal effects.

1. INTRODUCTION

1.1 Importance of multiphase flow in porous media

Multiphase flows in porous media occur in a variety of settings in applied science. The earliest applications involving the simultaneous flow of two fluids through a porous solid appear in the soil science literature, where the flow of water in soils partly occupied by air has fundamental importance¹²⁸. This unsaturated flow in some ways represents the simplest of multiphase flows. Yet, as we shall see, it exemplifies a fact underlying the continued growth in research in this area: multiphase flows in porous media are inherently nonlinear. Consequently, numerical simulation often furnishes the only effective strategy for understanding their behaviour quantitatively.

Although the earliest studies of multiphase flows in porous media concern unsaturated flows, the most concentrated research in this field over the past four decades has focused on flows in underground petroleum reservoirs. Natural oil deposits almost always contain connate water and occasionally contain free natural gas as well. The simultaneous flow of oil, gas and water in porous media therefore affects practically every aspect of the reservoir engineer's job of optimizing the recovery of hydrocarbons. Here, again, the physics of multiphase fluid flows give rise to nonlinear governing equations. The difficulty imposed by the nonlinearities along with the irregular geometries and transient behaviour associated with typical oil reservoirs make numerical simulation an essential tool in petroleum engineering. The advent of various enhanced oil recovery technologies has added to this field further levels of complexity and hence an even greater degree of reliance on numerical methods.

Most recently, multiphase flows have generated serious interest among hydrologists concerned with groundwater quality. There is growing awareness that many contaminants threatening our groundwater resources enter water-bearing rock formations as separate, nonaqueous phases. These oily liquids may come from underground or near-surface storage facilities, land-fills at which chemical wastes are dumped, industrial sites such as oil refineries or wood-treatment plants, or illegal waste disposal. Regardless of the source of the contaminants, our ability to understand and predict their flows underground is crucial to the design of sound remedial measures. This is a fairly new frontier in multiphase porous-media flows, and again the inherent complexity of the physics leads to governing equations for which the only practical way to produce solutions may be numerical simulation.

85-37

1.2 Scope of the article

The purpose of this article is to review some of the more salient applications of numerical simultation in multiphase porous-media flows. In light of the history and breadth of these applications, a review of this kind must choose between the impossibly ambitious goal of thoroughness and the risks of narrowness that accompany selective coverage. This article steers toward selective coverage. The aim here is to survey several multiphase flows that have attracted substantial scientific interest and to discuss a few aspects of their numerical simulation that have appeared in the recent technical literature. I confess at the outset that some important multiphase flows receive no attention here at all, and, even for the flows discussed, many potentially far-reaching contributions to numerical simulation get no mention. Perhaps the references given throughout the article can compensate in part for these shortcomings.

In particular, we shall restrict our attention here to underground flows in natural porous media. This

Accepted August 1985. Discussion closes February 1986

restriction excludes many applications in chemical engineering, one notable example being flows in packed beds of catalysts. Also, the article considers only isothermal flows. Therefore we do not discuss steamwater flows in geothermal reservoirs or such thermal methods of enhanced oil recovery as steam injection or fireflooding. Several numerical methods also receive scant or no mention. Among these are integrated finite differences, subdomain finite elements, spectral methods, and boundary-element techniques. Some of these approaches undoubtedly hold promise for future applications in multiphase flows in porous media. For the present, however, we concentrate on developments based on the trinity of more standard discrete approximations: finite differences, Galerkin finite elements and collocation.

2. BACKGROUND

2.1 Definitions

From a quantitative point of view, one of the most fruitful ways of examining multiphase flows in porous media is through the framework of continuum mixture theory. In contrast to a single continuum, a *mixture* is a set of overlapping continua called *constituents*. Any point in a mixture can in principle be the locus of material from each constituent, and each constituent possesses its own kinematic and kinetic variables such as density, velocity, stress and so forth. How one decomposes a physical mixture into constituents depends largely on one's theoretical aims, but in analysing porous media we commonly identify the solid matrix as one constituent and each of the fluids occupying its interstices as another.

In discussions of porous-media physics it is important distinguish between multiphase mixtures and to multispecies mixtures. A mixture consists of several phases if, on a microscopic length scale comparable, say, to typical pore apertures, one observes sharp interfaces in material properties. In this sense all porous-media flows involve multiphase mixtures, owing to the distinct boundary between the solid matrix and the interstitial fluids. At this boundary, density, for example, changes abruptly from its value in the solid to that in the fluid. More complicated multiphase mixtures occur, common examples being the simultaneous flows of air and water, oil and water, or oil and gas through porous rock. Here, in addition to rock-fluid interfaces, we observe interfaces between the various immiscible fluids at the microscopic scale. While the detailed structures of these interfaces and the volumes they bound are inaccessible to macroscopic observation, their geometry influences the mechanics of the mixture. This, at least intuitively, is why volume fractions play an important role in multiphase mixture theory. The volume fraction ϕ_{α} of phase α is a dimensionless scalar function of position and time such that $0 \leq \phi_{\alpha} \leq 1$, and, for any spatial region \Re in the mixture, $\int_{\mathscr{R}} \phi_{\alpha} \, d\mathbf{x}$ gives the fraction of the volume of \mathscr{R} occupied by phase α . The sum of the fluid volume fractions in a saturated solid matrix is the *porosity* ϕ .

On the other hand, there are mixtures in which no microscopic interfaces appear. Saltwater is an example. Here the constituents are ionic or chemical *species*, and spatial segregation of these constituents is not observable except, perhaps, at intermolecular length scales. Air is another multispecies mixture, consisting of N_2 , O_2 , CO_2 , and some trace gases. Multispecies mixtures differ from

multiphase mixtures in that volume fractions do not appear in the kinematics of the former.

It is possible to have multiphase, multispecies mixtures. These *compositional flows* occur in porous-media physics when there are several fluid phases, each of which comprises several chemical species. Such mixtures arise in many flows of practical interest, two important examples being multiple-contact miscible displacement in oil reservoirs and the contamination of groundwater by nonaqueous liquids. In these cases the transfer of chemical species between phases is a salient feature of the mixture mechanics. More detailed treatment of compositional flows appears later in this article.

2.2 Review of the basic physics

While the theory of mixtures dates at least to Eringen and Ingram⁶¹, its foundations are still the focus of active inquiry, as reviewed by Atkin and Craine¹⁷. Among the applications of mixture theory to multiphase mixtures and porous media are investigations by Prévost¹²⁴, Bowen^{29,30}, Passman, Nunziato and Walsh¹¹² and Raats¹²⁶. The aims of the present article in this respect are much more limited in scope than those just cited. What follows is a brief review of the basic physics of multiphase flows in porous media, using the language of mixture theory as a vehicle for the development of governing equations⁷.

For concreteness, assume that the mixture under investigation has three phases: rock (R) and two fluids (N, W). (The extension of this exposition to mixtures with more fluid phases is straightforward.) Each phase α has its own intrinsic mass density ρ_{α} , measured in kg/m³; velocity \mathbf{v}_{α} , measured in m/s; and volume fraction ϕ_{α} . From their definitions, the volume fractions clearly must obey the constraint $\sum_{\alpha} \phi_{\alpha} = 1$. In terms of these mechanical variables, the mass balance for any particular phase α is

$$\frac{\partial}{\partial t} (\phi_{\alpha} \rho_{\alpha}) + \nabla \cdot (\phi_{\alpha} \rho_{\alpha} \mathbf{v}_{\alpha}) = r_{\alpha}$$
(1)

where r_{α} stands for the rate of mass transfer into phase α from other phases. To guarantee mass conservation in the overall mixture, the reaction rates must obey the constraint $\sum_{\alpha} r_{\alpha} = 0$.

We can rewrite equation (1) in a more common form by noting that the porosity is $\phi = 1 - \phi_R$ and defining the fluid saturations $S_N = \phi_N / \phi$, $S_W = \phi_W / \phi$. Thus

$$\frac{\partial}{\partial t} \left[(1-\phi)\rho_R \right] + \nabla \cdot \left[(1-\phi)\rho_R \mathbf{v}_R \right] = r_R$$

for the rock phase, and

$$\frac{\partial}{\partial t}(\phi S_{\alpha}\rho_{\alpha}) + \nabla \cdot (\phi S_{\alpha}\rho_{\alpha}\mathbf{v}_{\alpha}) = r_{\alpha}, \qquad \alpha = N, \quad U$$
(2)

for the fluids.

Each phase also obeys a momentum balance. In its primitive form this equation relates the phase's inertia to its stress \mathbf{t}_{α} , body forces \mathbf{b}_{α} , and rate \mathbf{m}_{α} of momentum exchange from other phases. Thus,

$$\phi_{\alpha}\rho_{\alpha}\left(\frac{\partial\mathbf{v}_{\alpha}}{\partial t}+\mathbf{v}_{\alpha}\cdot\nabla\mathbf{v}_{\alpha}\right)-\nabla\cdot\mathbf{t}_{\alpha}-\phi_{\alpha}\rho_{\alpha}\mathbf{b}_{\alpha}=\mathbf{m}_{\alpha}-\mathbf{v}_{\alpha}\mathbf{r}_{\alpha}\qquad(3)$$

If we assume that the rock phase is chemically inert, so $r_R = 0$, and fix a coordinate system in which $\mathbf{v}_R = \mathbf{0}$, then the momentum balance for rock reduces to

$$7 \cdot \mathbf{t}_R - \phi_R \rho_R \mathbf{b}_R = \mathbf{m}_R$$

Let us assume that each fluid is Newtonian and that momentum transfer via shear stresses within the fluid is negligible compared with momentum exchange to the rock matrix. In this case $\mathbf{t}_{\alpha} = -p_{\alpha}\mathbf{1}$, where p_{α} is the *mechanical pressure* in fluid α and $\mathbf{1}$ is the unit isotropic tensor. If gravity is the only body force acting on fluid phase α , then $\phi_{\alpha}\mathbf{b}_{\alpha} = g\nabla Z$, where g stands for the magnitude of gravitational acceleration and Z represents depth below some datum. For the momentum exchange terms, the assumption common to most theories of porous media is that momentum losses to the solid matrix take the form of possibly anisotropic Stokes drags,

$$\Lambda_{\alpha}\mathbf{m}_{\alpha} = \phi(\mathbf{v}_{R} - \mathbf{v}_{\alpha}) = -\phi \mathbf{v}_{\alpha}$$

where Λ_{α} is a tensor called the *mobility* of phase α . If we assume further that the inertial effects in the fluid are negligible compared with rock-fluid interactions and that there is no interphase mass transfer, then equation (3) yields

$$\mathbf{v}_{\alpha} = -\frac{\mathbf{\Lambda}_{\alpha}}{\phi S_{\alpha}} \left(\nabla p_{\alpha} - \rho_{\alpha} g \nabla Z \right) \tag{4}$$

which is familiar as Darcy's law.

Clearly, the mobility Λ_{α} appearing in equation (4) accounts for much of the predictive power of Darcy's law in any particular rock-fluid system. Constitutive laws for mobility are largely phenomenological, the most common versions having the form $\Lambda_{\alpha} = \mathbf{k}k_{r\alpha}/\mu_{\alpha}$, where μ_{α} is the dynamic viscosity of fluid phase α , **k** is the *permeability*, and the *relative permeability* $k_{r\alpha}$ is a coefficient describing the effects of other fluids in obstructing the flow of fluid α .

For a two-fluid system with no interphase mass transfer, the relative permeabilities typically vary with saturation, and the curves $k_{rN}(S_W)$, $k_{rW}(S_W)$ look roughly like those drawn in Fig. 1¹⁰². The vanishing-point saturations S_{Nr} and S_{Wr} are called *residual* or *irreducible* saturations, and they account for the fact that, for a particular fluid to flow, it must be present at a sufficient degree of saturation to permit the formation of connected flow channels consisting of that phase. Actually, this picture of relative permeabilities is quite simplistic. In nature relative permeabilities often exhibit significant hysteresis, and the verification of the relative-permeability model in the presence of three or more fluid phases^{92,144,101} or compositional effects^{22,14} is still not clear.

Equation (4) allows each fluid phase to have its own pressure at any point in the reservoir. These pressure differences indeed occur in nature. At the microscopic scale the effects of interfacial tension and pore geometry on the curvatures of fluid-fluid interfaces lead to capillary effects. Leverett⁹¹ uses the classical thermodynamics of Gibbs⁷⁵ to describe these effects, while more recent works such as those of Morrow¹⁰³ and Davis and Scriven⁵¹ drawn connections with microscopic effects and molecular theories of interfacial tension. These theories imply that, at a macroscopic scale, there will be a pressure difference, or *capillary pressure*, between any two fluid phases in a porous medium. In two-phase systems, for example, there is a single capillary pressure $p_{CNW} = p_N - p_W$. In simple models p_{CNW} is a function of saturation; however, in actual flows the capillary pressure exhibits rather pronounced hysteresis^{103,82,134} and dependence on fluid composition⁴².

Given velocity field equations such as equation (4), we can expand the mass balances for the fluid phases to get flow equations for each fluid. Using the customary decomposition of the mobility Λ_{α} and directly substituting equation (4) into equation (2) yields, for a two-phase system,

$$\frac{\partial}{\partial t}(\phi S_N \rho_N) - \nabla \cdot \left[\frac{\rho_N \mathbf{k} k_{rN}}{\mu_N} \left(\nabla p_W + \nabla p_{CNW} - \rho_N g \nabla Z\right)\right] = 0$$

$$\frac{\partial}{\partial t}(\phi S_W \rho_W) - \nabla \cdot \left[\frac{\rho_W \mathbf{k} k_{rW}}{\mu_W} \left(\nabla p_W - \rho_N g \nabla Z\right)\right] = 0$$
(5)

Flow equations for systems having more fluid phases will be similar, except that if P phases coexist, then P-1independent capillary pressure functions will appear in the system.

2.3 Early investigations

The picture of multiphase flows in porous media outlined above evolved over several decades beginning in the 1930s. The use of an extended version of the singlephase form of Darcy's law in multiphase flows appears to have begun with Richards¹²⁸ in his work on unsaturated flows in the soil physics literature. The explicit use of a separate velocity field equation for each fluid began in the petroleum industry. Here the pioneering work of Muskat *et al.*¹⁰⁴, Wykoff and Botset¹⁶¹, Buckley and Leverett³⁴, Fatt and Dykstra⁶⁸ and Welge¹⁵⁹, among others, promoted the widespread acceptance of Darcy's equation altered by the incorporation of relative permeabilities. Today this model is the one most widely used in the prediction of multiphase flows in porous media.

Despite its broad appeal in applications, the multiphase version of Darcy's law has some limitations.



Fig. 1. Typical relative permeability curves¹⁰²

Relative permeabilities are not strictly functions of saturation, the most glaring violation being the phenomenon of hysteresis or dependence on saturation history. Such microscopic phenomena as gas slippage at the solid walls, turbulence, and adsorption can also invalidate the Darcy model in certain flows³³. These limitations are worthy of consideration in the application of the multiphase Darcy law to any new rock-fluid system.

3. TWO-PHASE FLOWS

The simplest multiphase flows in porous media are those in which two fluids flow simultaneously but do not exchange mass or react with the solid matrix. While many flows of practical interest exhibit more complex physics, two-phase flows have drawn attention in many applications. Among these are unsaturated groundwater flows, salt-water intrusion in coastal aquifers, and the Buckley-Leverett problem in petroleum engineering.

3.1 Unsaturated groundwater flow

In typical soil profiles some distance separates the earth's surface from the water table, which is the upper limit of completely water-saturated soil. In this invervening zone the water saturation varies between 0 and 1, the rest of the pore space normally being occupied by air. Water flow in this *unsaturated zone* is complicated by the fact that the soil's permeability to water depends on its water saturation. Let us derive the common form of the governing equation and examine some of the computational difficulties that arise in its solution.

Most formulations of unsaturated flow rest on the assumption that the motion of air has negligible effect on the motion of water. Therefore one usually neglects the flow equation for air, assuming that the air pressure equals the constant atmospheric pressure at the surface, that is, $p_A = p_{atm}$. Then we can define the *pressure head* in the water by $\psi = (p_W - p_A)/(\rho_W g)$, having the dimensions of length and being negative in the unsaturated zone where $S_W < 1$. Also, instead of saturation, soil physicists typically refer to the soil's *moisture content*, defined by $\Theta = \phi S_W$. In terms of these new variables the capillary pressure relationship for the air-water system becomes $\psi = \psi(\Theta)$ or, provided ψ is an invertible function, $\Theta = \Theta(\psi)$. From equation (5b), the flow equation for water thus transforms to

$$\frac{\partial}{\partial t} \left(\Theta \rho_{W} \right) = \nabla \cdot \left[\mathbf{K} \cdot \rho_{W} (\nabla \psi + \nabla Z) \right]$$

where $\mathbf{K} = \rho_W g \mathbf{k} k_{rW} / \mu_W$ is the hydraulic conductivity of the soil. Notice that **K** is a function of ψ , since relative permeability depends on saturation, which varies with ψ according to the capillarity relationship.

In many unsaturated flows the compressibility effects in water are small, so that time derivatives and spatial gradients of ρ_W may be neglected. If this approximation holds, then the flow equation reduces to

$$\frac{\partial \Theta}{\partial t} = \nabla \cdot \left[\mathbf{K} \cdot (\nabla \psi + \nabla Z) \right] \tag{6}$$

To get an equation in which ψ is the principal unknown, we simply use the chain rule to expand the time derivative

on the left, giving

$$C(\psi) \frac{\partial \psi}{\partial t} = \nabla \cdot \left[\mathbf{K}(\psi) (\nabla \psi + \nabla Z) \right]$$

where $C(\psi) = d\Theta/d\psi$ is the specific moisture capacity. If the flow is essentially one-dimensional in the vertical direction, then this equation collapses to

$$C(\psi) \frac{\partial \psi}{\partial t} = \frac{\partial}{\partial z} \left[K(\psi) \left(\frac{\partial \psi}{\partial z} + 1 \right) \right]$$
(7)

which is Richards' equation¹²⁸.

Several investigators in hydrology have examined the unsaturated flow equation from analytic viewpoints. Philip¹¹⁹ gives one of the earliest theoretical treatments of Richards' equation, proposing asymptotic solutions for a nonlinear problem. The equation has also attracted interest in the applied mathematics community, including investigations by Aronson¹⁶, Peletier¹¹⁶ and Nakano¹⁰ Aronson¹⁶, for example, observes that, while the classical linear heat equation admits solutions in which disturbances propagate with infinite speeds, the nonlinear equation (7) may propagate disturbances with only finite speed. This implies that a moving interface, or wetting front, can form between the downward-moving zone of high moisture content Θ and the zone yet uncontacted by the wave of infiltrating water. Under certain initial conditions this moving boundary can exhibit steep spatial gradients in Θ and consequently in ψ . The resulting sharp fronts pose considerable difficulty in the construction of numerical schemes, since the discrete approximations used typically have lowest-order error terms that increase with the norm of the solution's gradient. We shall discuss this difficulty in more detail in Section 6.

Numerical work by a variety of investigators has corroborated the existence of wetting fronts. Much of this work appeared during the 1970s, and it includes articles by Bresler³³, Neuman¹⁰⁷, Reeves and Duguid¹²⁷, Narasimhan and Witherspoon¹⁰⁶ and Segol¹³⁶. Van Genuchten^{151,152} presents solution schemes for the oneand two-dimensional versions of Richards' equation using both finite differences and finite-element Galerkin methods employing Hermite cubic basis functions. His work furnishes a good comparison of the finite-difference and finite-element approaches to the approximation of wetting fronts.

Van Genuchten's investigation also demonstrates another difficulty in solving Richards' equation numerically. This problem owes its existence to the nonlinear coefficient $C(\psi)$ appearing in the accumulation term of equation (7). Because the equation itself is nonlinear, implicit time-stepping algorithms must incorporate an iterative procedure for advancing the approximate solution from one time step to the next. There then arises a question regarding the proper time level at which to evaluate $C(\psi)$. Van Genuchten demonstrates that evaluating this coefficient in a fully implicit fashion can lead to material balance errors in certain schemes, among them the Galerkin scheme using two-point Gauss quadrature to evaluate the mass and stiffness matrix elements. Figure 2 shows how this scheme produces a wetting front that lags the true solution. Milly⁹⁹ advances an iterative method for evaluating $C(\psi)$



Fig. 2. Solutions to the unsaturated flow equation using various finite-element Galerkin schemes¹⁵¹

at the correct time level to guarantee good global material balances.

Allen and Murphy¹¹ propose another approach to the time-stepping problem in unsaturated flows. While the method is used in connection with finite-element collocation – a technique closely related to the two-point Gauss quadrature scheme mentioned above – the basic idea should be applicable with most spatial discretizations. If we return to the original form of the accumulation term, equation (7) becomes

$$\frac{\partial \Theta}{\partial t} = \frac{\partial}{\partial z} \left[K(\psi) \left(\frac{\partial \psi}{\partial z} + 1 \right) \right]$$

One can circumvent the difficulties encountered in solving an equation in both Θ and ψ by properly formulating an iterative procedure. Let us approximate the time derivative using implicit finite differences:

$$\frac{\Theta(\psi^{n+1}) - \Theta(\psi^n)}{\Delta t} = \frac{\partial}{\partial z} \left[K(\psi^{n+1}) \left(\frac{\partial \psi^{n+1}}{\partial z} + 1 \right) \right] + \mathcal{O}(\Delta t)$$

We can linearize the flux terms in this approximation by establishing an iterative scheme in which $\psi^{n+1,m}$ represents the value of ψ at the most recent known iteration level and $\psi^{n+1,m+1} = \psi^{n+1,m} + \delta \psi^{n+1,m+1}$ represents the value at the sought iterative level:

$$\frac{\partial}{\partial z} \left\{ K(\psi^{n+1,m}) \left[\frac{\partial}{\partial z} \left(\psi^{n+1,m} + \delta \psi^{n+1,m+1} \right) + 1 \right] \right\}$$

This expression allows the nonlinear coefficient $K(\psi^{n+1})$ to lag by an iteration.

In the accumulation term we also lag $\Theta(\psi^{n+1})$, but in addition we linearly project forward to the next iterative level using the Newton-like extrapolation

$$\frac{1}{\Delta t} \left[\Theta(\psi^{n+1,m}) + C(\psi^{n+1,m}) \delta \psi^{n+1,m+1} - \Theta(\psi^n) \right]$$

Here, recall that $C(\psi) = d\Theta/d\psi$. The value ψ^n of pressure head at the old time level represents the value furnished by the iterative scheme after convergence, which a computer code can test using either of two criteria. First, one can check whether the iterative increment $\delta\psi^{n+1,m+1}$ is small enough in magnitude or norm to warrant stopping the iteration. Second, one can observe that collecting the terms involving the unknown $\delta\psi^{n+1,m+1}$ on the left and ignoring truncation error leaves the known quantity

$$-\frac{\Theta(\psi^{n+1,m}) - \Theta(\psi^n)}{\Delta t} + \frac{\partial}{\partial z} \left[K(\psi^{n+1,m}) \left(\frac{\partial \psi^{n+1,m}}{\partial z} + 1 \right) \right]$$
$$\equiv -R^{n+1,m}$$

acting as a right-hand side in the linearization. This quantity is precisely the residual to the flow equation at the *m*th iteration. Whenever $||R^{n+1,m}||$ is small in some appropriate norm, the resulting increment $\delta \psi^{n+1,m+1}$ will be small and, more to the point, we shall have solved the time-differenced equation to within a very small error.

It is easy to see why such a scheme conserves mass, at least to within limits imposed by the iterative convergence criteria. If we integrate the residual $R^{n+1,m}(z)$ over the spatial domain Ω of the problem, we find

$$-\int_{\Omega} \frac{\Theta(\psi^{n+1,m}) - \Theta(\psi^n)}{\Delta t} \, \mathrm{d}z + K(\psi^{n+1,m}) \left(\frac{\partial \psi^{n+1,m}}{\partial z} + 1\right) \Big|_{\partial\Omega}$$
$$= -\int_{\Omega} R^{n+1,m} \, \mathrm{d}z$$

If the integral on the right were zero, this equation would be precisely the global mass balance for vertical unsaturated flow. Thus by iterating until $||R^{n+1,m}||$ is small, we implicitly enforce the global mass balance to a desired level of accuracy.

3.2 Saltwater intrusion

In coastal aquifers both fresh water and salt water are usually present. Being denser, the salt water underlies the fresh water, the latter forming a lens whose shape and thickness may vary with changes in pumping and recharge. Figure 3 depicts a typical coastal aquifer in cross-section. When the upper portion of the aquifer acts as a source of fresh water, it becomes important to design pumping and recharge strategies that prevent the flow of salt water into production wells.

Strictly speaking, salt water and fresh water are not separate phases. In fact they are completely miscible as fluids, and in a coastal aquifer there exists a zone lying between the two fluids in which salt concentration varies continuously. To be rigorously faithful to the physics of the problem, then, one would solve a single-phase flow equation coupled with a transport equation for salt. Indeed, one of the earliest numerical treatments of



Fig. 3. Schematic cross-section of a coastal aquifer⁸⁴

saltwater intrusion used just this approach¹²⁰. Nevertheless, the transition zone between salt and fresh water is often quite narrow in comparison with the overall thickness of the aquifer, and for computational purposes we may consider it to be a sharp interface. Such a sharpinterface approximation serves as justification for treating saltwater intrusion into coastal aquifers as a multiphase flow.

Let us consider the problem of modelling the areal movement of salt and fresh water. To get vertically averaged flow equations, we first write the equations in terms of *hydraulic heads*, defined in the fresh water (F) and salt water (S) as follows:

$$h_{\alpha} = \frac{1}{g} \int_{p_{ref}}^{p_{\alpha}} \frac{\mathrm{d}p'}{\rho_{\alpha}(p')} + z \qquad \alpha = F \text{ or } S$$

is the effective rate of withdrawal from the freshwater zone, and

$$q_F|_{z=b} = -(\mathbf{v}_F - \phi \mathbf{v}_{\Sigma})|_{z=b} \cdot (\mathbf{e}_z - \nabla b)$$

is the effective rate of exchange of freshwater across the interface Σ , which we have assumed to be zero.

A similar development for salt water leads to the vertically averaged flow equation

$$\overline{\nabla} \cdot (T_S \overline{\nabla} \overline{h}_S) + q_S|_{z=b} - q_S|_{z=a} = C_S \frac{\partial \overline{h}_S}{\partial t} + \phi \frac{\partial b}{\partial t} \qquad (10)$$

Here $T_s = K_s l_s$ and $C_s = S_{s,s} l_s$. The sink terms in this equation are

$$q_{S}|_{z=b} = -(\mathbf{v}_{S} - \phi \mathbf{v}_{\Sigma})|_{z=b} \cdot (\mathbf{e}_{z} - \nabla b)$$

which represents the effective rate of withdrawal from the saltwater zone, and

$$q_{S}|_{z=a} = -\mathbf{v}_{S}|_{z=a} \cdot (\mathbf{e}_{z} - \nabla a)$$

which gives the effective rate of saltwater leakage into the lower confining layer, whose depth is fixed.

To solve this system we need an equation relating \bar{h}_F and \bar{h}_S . In this case, since the two fluids are miscible at the microscopic scale, there will be no head difference between the fluids where they are in contact. Thus the head is continuous across the interface Σ : $h_F = h_S$ at z = b. As Huyakorn and Pinder⁸⁴ show, this condition allows us to solve for $\partial b/\partial t$ in terms of heads:

$$\frac{\partial b}{\partial t} = \rho_S^* \frac{\partial \bar{h}_S}{\partial t} - \rho_F^* \frac{\partial \bar{h}_F}{\partial t}$$
(11)

where $\rho_{\alpha}^* = \rho_{\alpha}/(\rho_S - \rho_F)$. Combining equation (11) with equations (9) and (10) yields the coupled system of flow equations

$$\nabla \cdot \begin{bmatrix} T_F & 0 \\ 0 & T_S \end{bmatrix} \nabla \begin{bmatrix} \bar{h}_F \\ \bar{h}_S \end{bmatrix} + \begin{bmatrix} q_F|_{z=c} \\ q_S|_{z=b} - q_S|_{z=a} \end{bmatrix}$$
$$= \begin{bmatrix} C_F + \phi \rho_F^* & -\phi \rho_S^* \\ -\phi \rho_F^* & C_S + \phi \rho_S^* \end{bmatrix} \frac{\partial}{\partial t} \begin{bmatrix} \bar{h}_F \\ \bar{h}_S \end{bmatrix} \quad (12)$$

Let us examine the approximate numerical solution to equation (12) using finite-element Galerkin methods. In these methods we replace the unknown functions $\bar{h}_F(\mathbf{x}, t)$ and $\bar{h}_S(\mathbf{x}, t)$ by trial functions

$$\hat{h}_F(\mathbf{x}, t) = h_{F,\hat{o}}(\mathbf{x}, t) + \sum_{i=1}^{I} h_{F,i}(t)N_i(\mathbf{x})$$
$$\hat{h}_S(\mathbf{x}, t) = h_{S,\hat{o}}(\mathbf{x}, t) + \sum_{i=1}^{I} h_{S,i}(t)N_i(\mathbf{x})$$

The functions $h_{F,\partial}$ and $h_{S,\partial}$ satisfy the essential boundary conditions for the problem at hand, and each of the sums on the right satisfies homogeneous boundary conditions. For continuous interpolating trial functions, $h_{F,i}(t)$ and $h_{S,i}(t)$ usually stand for the values of head at the *i*th spatial node, while the *basis functions* $N_i(\mathbf{x})$ dictate the variation between nodes.

To form the Galerkin equations corresponding to equation (12), we substitute \hat{h}_F and \hat{h}_S for \bar{h}_F and \bar{h}_S in equation (12), multiply each equation by each of the basis functions $N_1(\mathbf{x}), \ldots, N_I(\mathbf{x})$, and force the integral of the result over the spatial domain Ω to vanish. Doing this leads to time evolution equations for the unknown nodal values $h_{F,i}(t)$ and $h_{S,i}(t)$. For the freshwater equation, there results

$$\sum_{i=1}^{I} \left(K_{ij}^{F} h_{F,i} - Q_{ij}^{F} h_{F,i} + M_{ij}^{F,i} \frac{dh_{V,i}}{dt} + M_{ij}^{F,2} \frac{dh_{S,i}}{dt} \right) + \int_{\Omega} q_{F}|_{z=c} N_{j} d\mathbf{x} = B_{j}^{F} \qquad j = 1, \dots, I$$

where K_{ij}^F , Q_{ij}^F , $M_{ij}^{F,1}$, $M_{ij}^{F,2}$ and B_j^F have the meanings assigned in Table 1.

A similar collection of evolution equations arises from the saltwater flow equation:

$$\sum_{i=1}^{I} \left(K_{ij}^{S} h_{S,i} - Q_{ij}^{S} h_{S,i} + M_{ij}^{S,1} \frac{\mathrm{d}h_{F,i}}{\mathrm{d}t} + M_{ij}^{S,2} \frac{\mathrm{d}h_{S,i}}{\mathrm{d}t} \right) + \int_{\Omega} (q_{S}|_{z=b} - q_{S}|_{z=a}) N_{j} \,\mathrm{d}\mathbf{x} = B_{j}^{S} \qquad j = 1, \dots, I$$

where the definitions of K_{ij}^{S} , Q_{ij}^{S} , $M_{ij}^{S,1}$, $M_{ij}^{S,2}$ and B_{j}^{S} again appear in Table 1. Rewriting this set of 2*I* evolution equations in matrix form gives a system having the structure

$$[K]{h} + [M] \frac{\partial}{\partial t} {h} = {r}$$
(13)

Table 1. Galerkin integrals appearing in the saltwater intrusion equations

$$\begin{split} K_{ij}^{F} &= \int_{\Omega} T_{F} \nabla N_{i} \cdot \nabla N_{j} \, \mathrm{dx} \\ Q_{ij}^{F} &= \oint_{\partial \Omega} T_{F} N_{j} \nabla N_{i} \cdot \mathbf{n} \, \mathrm{dx} \\ M_{ij}^{F,1} &= -\int_{\Omega} (C_{F} + \phi \rho_{F}^{*}) N_{i} N_{j} \, \mathrm{dx} \\ M_{ij}^{F,2} &= \int_{\Omega} \phi \rho_{S}^{*} N_{i} N_{j} \, \mathrm{dx} \\ B_{j}^{F} &= -\int_{\Omega} T_{F} \nabla h_{F,\partial} \cdot \nabla N_{j} \, \mathrm{dx} + \oint_{\partial \Omega} N_{j} T_{F} \nabla h_{F,\partial} \cdot \mathbf{n} \, \mathrm{dx} \\ &+ \int_{\Omega} (C_{F} + \phi \rho_{F}^{*}) N_{j} \frac{\partial h_{F,\partial}}{\partial t} \, \mathrm{dx} - \int_{\Omega} \phi \rho_{S}^{*} N_{j} \frac{\partial h_{S,\partial}}{\partial t} \, \mathrm{dx} \\ K_{ij}^{S} &= \int_{\Omega} T_{F} \nabla N_{i} \cdot \nabla N_{j} \, \mathrm{dx} \\ Q_{ij}^{S} &= \oint_{\partial \Omega} T_{F} N_{j} \nabla N_{i} \cdot \mathbf{n} \, \mathrm{dx} \\ M_{ij}^{S,1} &= \int_{\Omega} \phi \rho_{F}^{*} N_{i} N_{j} \, \mathrm{dx} \\ M_{ij}^{S,2} &= -\int_{\Omega} (C_{S} + \phi \rho_{S}^{*}) N_{i} N_{j} \, \mathrm{dx} \\ B_{j}^{S} &= -\int_{\Omega} T_{S} \nabla h_{S,\partial} \cdot \nabla N_{j} \, \mathrm{dx} + \oint_{\partial \Omega} N_{j} T_{S} \nabla h_{S,\partial} \cdot \mathbf{n} \, \mathrm{dx} \\ &+ \int_{\Omega} (C_{S} + \phi \rho_{S}^{*}) N_{j} \frac{\partial h_{S,\partial}}{\partial t} \, \mathrm{dx} - \int_{\Omega} \phi \rho_{F}^{*} N_{j} \frac{\partial h_{F,\partial}}{\partial t} \, \mathrm{dx} \end{split}$$

where $\{h\}$ signifies a vector containing the 2*I* unknown nodal values of head, [K] and [M] are the stiffness and mass matrices arising from flux and accumulation terms, respectively, and $\{r\}$ is a vector containing known boundary data and withdrawal rates.

The system (13) is nonlinear, owing to the dependence of the zonal thicknesses l_F and l_S on the unknown heads. Thus any temporal discretization of these ordinary differential equations will have to be iterative in nature to guarantee consistency betweeh the numerical solution and the flow coefficients at each time level. Pinder and Page¹²¹ advance one such iterative scheme.

The saltwater interface problem exhibits a peculiar computational difficulty associated with the saltwaterfreshwater interface Σ . This problem manifests itself as the saltwater wedge retreats or advances. Under these circumstances the intersection of Σ with the lower confining layer, called the *saltwater toe*, moves horizontally. This moving boundary allows for the possibility that the interface may not exist at some areal locations, and at these locations the free surface condition becomes degenerate⁹⁷. To accommodate this degeneracy, it becomes necessary to track the moving boundary as the flow calculations proceed.

Shamir and Dagan¹³⁹ present a finite-difference algorithm for tracking the saltwater toe in a vertically integrated, immiscible setting. By examining a onedimensional flow, they develop a scheme for regnerating the spatial grid to guarantee that the toe lies on a computational node. Thus on the ocean side of the separating node they solve the simultaneous flow equations for saltwater and freshwater heads, while on the inland side they solve the equation for freshwater head only. This approach obviously involves a great deal of computational complexity in two or three dimensions, since it requires the construction of multidimensional moving finite-difference grids. However, an analogous idea for finite-element grids in two dimensions has proved promising⁵⁵.

In another approach, Sá da Costa and Wilson¹³¹ use a fixed, two-dimensional, quadrilateral finite-element grid to model the immiscible flow equations. They devise a toe-tracking algorithm based on the Gauss points used to compute the integrals contributing to the matrix entries in equation (13). At Gauss points inland of the toe the model assigns a very small nonzero saltwater transmissibility T_s . Thus, while the saltwater wedge never actually disappears in the numerical scheme, inland of the toe the flow of salt water is negligible.

3.3 The Buckley–Leverett problem

The Buckley–Leverett problem serves as a fairly simple model of two-phase flow in a porous medium. The problem, introduced by Buckley and Leverett³⁴, has particular relevance in the petroleum industry, where gas and water injection are two common techniques for displacing oil toward production wells in underground reservoirs. The simplicity of the Buckley-Leverett problem arises from three basic assumptions. First, the total flow rate of oil and displacing fluid (say water) remains constant. Second, the rock matrix and fluids are incompressible. Third, the effects of capillary pressure gradients on the flow field are negligible compared with the pressure gradients applied through pumping. These assumptions are too restrictive to permit widespread application of the Buckley-Leverett model, but, as we shall argue below, the simplified model acts as a paradigm for the numerical difficulties that occur in more complicated models of oil reservoirs.

To derive the Buckley-Leverett model, we begin with equation (5), identifying N as oil and W as water and assuming an isotropic porous medium:

$$\frac{\partial}{\partial t} (\phi S_N \rho_N) - \nabla \cdot [\rho_N \Lambda_N (\nabla p_W + \nabla p_{CNW} - \rho_N g \nabla Z)] = 0$$
$$\frac{\partial}{\partial t} (\phi S_W \rho_W) - \nabla \cdot [\rho_W \Lambda_W (\nabla p_W - \rho_W g \nabla Z)] = 0$$

where $\Lambda_{\alpha} = kk_{r\alpha}/\mu_{\alpha}$ is the mobility of fluid α . Coupled to these flow equations are the constraint $S_N + S_W = 1$ and a capillary relationship $p_{CNW} = p_{CNW}(S_W)$. If we restrict our attention to one-dimensional flow in a homogeneous reservoir of uniform cross-section and assume that gravity effects are absent, then the flow equations collapse to

$$\frac{\partial}{\partial t}(\phi S_N \rho_N) - \frac{\partial}{\partial x} \left[\rho_N \Lambda_N \left(\frac{\partial p_W}{\partial x} + \frac{\partial p_{CNW}}{\partial x} \right) \right] = 0$$
$$\frac{\partial}{\partial t}(\phi S_W \rho_W) - \frac{\partial}{\partial x} \left(\rho_W \Lambda_W \frac{\partial p_W}{\partial x} \right) = 0$$

Now we invoke the assumption that capillarity has negligible effect on the flow field-wide, so that $\partial p_{CNW}/\partial x \simeq 0$. Further, the incompressibility assumption implies that ϕ , ρ_N and ρ_W are constant in time and that the fluid densities are uniform in space, so that

$$\phi \frac{\partial}{\partial t} (1 - S_w) - \frac{\partial}{\partial x} \left(\Lambda_N \frac{\partial p_w}{\partial x} \right) = 0 \qquad (14a)$$

$$\phi \frac{\partial S_W}{\partial t} - \frac{\partial}{\partial x} \left(\Lambda_W \frac{\partial p_W}{\partial x} \right) = 0 \qquad (14b)$$

Now observe that $-\Lambda_{\alpha}\partial p_w/\partial x$ is the Darcy flux q_{α} of phase α . Also, by assumption, the total flow rate $q = q_w + q_N$ is a constant. Thus we need only solve one of equations (14), using the constant value of q to solve the other equation by subtraction.

Let us solve the water equation (14b). Since $-\Lambda_W \partial p_W / \partial x = q_W = \Lambda_W q / (\Lambda_W + \Lambda_N)$, we arrive at the Buckley-Leverett saturation equation

$$\frac{\partial S_W}{\partial t} + \frac{\partial}{\partial x} \left(\frac{qf_W}{\phi} \right) = 0 \tag{15}$$

where $f_W = \Lambda_W / (\Lambda_N + \Lambda_W)$ is the *fractional flow* of water. Equation (15) is clearly nonlinear, since f_W depends on the unknown water saturation S_W through the fluid mobilities. While the functional form of $f_W(S_W)$ depends on the particular rock-fluid system being modelled, fractional flow functions typically have an 'S-shaped' profile over their supports $(S_{Wr}, 1 - S_{Nr})$, as shown in Fig. 4.

Difficulties in solving Cauchy problems involving equation (15) arise from two sources. First, the equation itself is a nonlinear, hyperbolic conservation law. Its hyperbolicity owes to our neglect of capillary pressure gradients, inclusion of which would have led to an additional second-order term of the form

$$\frac{\partial}{\partial x} \left[\phi^{-1} \Lambda_W p'_{CNW}(S_W) \frac{\partial S_W}{\partial x} \right]$$

Thus equation (15) is, in effect, an approximation to a singularly perturbed parabolic problem in which we have neglected the dissipative effects of capillarity.

Second, the flux function qf_W/ϕ appearing in equation (15) is nonconvex, its S-shaped form implying the existence of an inflection point somewhere in its support. The literature on hyperbolic conservation laws with nonconvex flux functions is quite extensive, including important contributions by Lax⁹⁰ and Oleinik¹¹¹ and a general discussion by Chorin and Marsden³⁹. Of special importance in the present context are the following facts. Cauchy problems based on equation (15) may have no solutions that are classical in the sense of being continuously differentiable over their (x,t)-domains $\Omega \times J$. Instead, such problems may admit only weak solutions $S_W(x, t)$. These solutions need only satisfy the integral relation

$$\int_{\Omega \times J} \left[S_W \frac{\partial \varphi}{\partial t} + \frac{q}{\phi} f_W(S_W) \frac{\partial \varphi}{\partial x} \right] dx \, dt = 0$$
 (16)

for all infinitely differentiable functions $\varphi(x, t)$ that vanish on the boundary $\partial(\Omega \times J)^{126}$. In contrast to equation (15), equation (16) admits functions $S_W(x, t)$ that have discontinuities, or saturation shocks. Unfortunately, weak solutions may not be unique: there may be several different functions $S_W(x,t)$ that satisfy the integral equation (16).

Nature admits only one solution to the Buckley-Leverett problem. Much of the research into hyperbolic conservation laws has aimed at identifying physically correct weak solutions from among the class of functions obeying equation (16). To specify the physical solution requires an additional constraint known as the *entropy condition*. There are several equivalent forms of this constraint, including the following¹³:

- (i) The solution must depend continuously and stably on the initial data, implying that characteristics on both sides of a discontinuity must intersect the initial curve.
- (ii) The solution must be the same as that obtained using the method of characteristics with $f_W(S_W)$ replaced by its convex hull.
- (iii) The solution must be the limit of solutions, for the same initial data, to a parabolic problem differing from the hyperbolic one by a dissipative secondorder term (in this case, capillarity) of vanishing influence.

The tangent construction advanced by Welge¹⁵⁹ explicitly implements condition (ii) while, as Welge shows in his paper, the 'equal-area' rule of Buckley and Leverett³⁴ imposes this same constraint in a slightly different fashion.

Any numerical scheme for solving the Buckley– Leverett problem, or even more complicated models of multiphase flows that are hyperbolic in character, must respect the entropy condition or else risk producing nonphysical results. Douglas *et al.*⁵⁷, for example, propose adding an artificial capillarity to the Buckley– Leverett equation to force convergence to the correct physical solution. An equivalent effect can be achieved by using certain numerical approximations whose lowest-



Fig. 4. Typical nonconvex fractional flow fraction f and related convex functions¹³

order error terms mimic the desired dissipative phenomena⁸. This tactic is perhaps easiest to see in finitedifference approximations. Here, an upstream-biased difference analog of the flux term $\partial f/\partial x$ gives

$$\frac{f_i - f_{i-1}}{\Delta x} = \frac{\partial f}{\partial x}\Big|_i - \frac{\Delta x}{2} \frac{\partial}{\partial x} \left[f'(S) \frac{\partial S}{\partial x} \right]_i + \mathcal{O}(\Delta x^2)$$

Since f'(S) > 0 over the support of f, the lowest-order error term acts like the capillarity term neglected in equation (15) while vanishing linearly as $\Delta x \rightarrow 0$. Thus upstream weighting imposes a numerical version of condition (iii) while maintaining consistency in the numerical approximation.

Several investigators have examined upstreamweighted finite-element methods for the Buckley– Leverett problem. Mercer and Faust⁹⁶ and Huyakorn and Pinder⁸³, for example, discuss upstream-weighted Galerkin techniques. Shapiro and Pinder¹⁴⁰ advance a finite-element collocation scheme for the Buckley– Leverett problem using asymmetric basis functions.

Allen and Pinder^{12,13} introduce a collocation scheme for the same problem in which upstream biasing of the collocation points leads to the appropriate numerical version of condition (ii). To implement this method, we begin with a continuously differentiable trial function for saturation:

$$\hat{S}(x,t) = \sum_{i=0}^{l} \left[S_i(t) H_{0,i}(x) + S'_i(t) H_{1,i}(x) \right]$$

where the basis functions $H_{0,i}(x)$, $H_{1,i}(x)$ are piecewise Hermite cubic polynomials (5). $S_i(t)$, $S'_i(t)$ are the unknown nodal values of S_W and $\partial S_W/\partial x$, respectively. One can similarly represent the nonlinear flux function f_W :

$$\hat{f} = \sum_{i=1}^{l} \left[f_{W}(S_{i})H_{0,i} + \frac{\mathrm{d}f_{W}}{\mathrm{d}S_{W}}(S_{i})S_{i}'H_{1,i} \right]$$

In the standard collocation we derive ordinary differential equations for the unknown values S_i , S'_i , by setting

$$\frac{\partial \hat{S}}{\partial t}(\bar{x}_k, t) + \frac{q}{\phi} \frac{\partial \hat{f}}{\partial x}(\bar{x}_k, t) = 0$$

at enough points \bar{x}_k in the spatial domain to give one equation for each unknown. Douglas and Dupont⁵⁸ show that, on a uniform partition $x_0 < \cdots < x_I = x_0 + I \Delta x$, one can achieve $\mathcal{O}(\Delta x^4)$ accuracy in parabolic problems by choosing the Gauss points $x_i - \Delta x/2 \pm \Delta x/\sqrt{3}$, $i=1,\ldots, I-1$, as the collocation points. As Allen and Pinder¹³ demonstrate, however, this highly accurate scheme violates the entropy condition in equation (15). One can force convergence to the correct solution by evaluating the flux term at collocation points upstream of the Gauss points, as in the equation

$$\frac{\partial \hat{S}}{\partial t}(\bar{x}_{k},t) + \frac{q}{\phi}\frac{\partial \hat{f}}{\partial x}(\bar{x}_{k}^{*},t) = 0$$

Here, for flow in positive x direction, $\bar{x}_k^* < \bar{x}_k$. Allen⁷ presents an error analysis showing how this scheme introduces artificial capillarity. Figures 5 and 6 compare the results of standard collocation and upstream collocation, respectively.



Fig. 5. Solution to the Buckley-Leverett problem generated by orthogonal collocation with $\Delta x = 0.1^{12}$



Fig. 6. Solutions to the Buckley–Leverett problem generated by upstream collocation with $\Delta x = 0.1$, 0.05, 0.025^{12}

Several investigators have examined the use of upstream weighting in more sophisticated models of multiphase flow. Among the many such studies are those by Peacemen¹¹³, Settari and Aziz¹³⁷ and Young¹⁶⁴, each of which offers a good overview of numerical approximations used to model two-phase flows. We shall consider upstream weighting further in Section 4.

unfortunate aspect of upstream-biased One approximations is that their artificially dissipative effects, while guaranteeing convergence, produce unrealistically smeared sharp fronts when the spatial grid mesh is large. What is 'large' in this sense depends on the physics of the problem and not the computational resources of the modeller. Therefore, in some problems, unacceptable smearing on uniform grids can occur even when the grid mesh approaches limits in affordable fineness. One approach to resolving this dilemma is to refine the spatial grid only in the vicinity of the steep front. Since the front itself moves as the flow progresses, such a strategy calls for self-adaptive local grid refinement, a topic discussed in Section 6.

4. FLOWS WITH INTERPHASE MASS TRANSFER

In many multiphase flows of interest in engineering the exchange of chemical species among the fluid phases is crucial to the behaviour of the flows. Historically, concern with the compositional aspects of multiphase flows in porous media originated in the petroleum industry, where the effects of gas dissolution, retrograde condensation, and vaporization and condensation of injected gases have substantial implications in oil recovery operations. As the complexities of groundwater contamination by organic wastes become more urgent, however, interest in multiphase flows with mass transfer has spread to the hydrology community. In this section we shall focus on the more established modelling efforts in the petroleum industry, leaving discussion of the newer applications in hydrology to Section 5.

4.1 Compositional oil reservoir flows

In compositional flows there are several fluid phases in which some number of chemical species reside. It is therefore necessary to extend the mixture-theoretic formalism to accommodate two different categories of constituents: phases and species. A more detailed exposition of the development given below appears in Allen⁷. For simplicity, let us assume that there are three fluid phases, namely water (W), oil (O) and gas(G) with chemical species indexed by i = 1, ..., N + 1. As before, let us label the rock phase by the index R. Conceivably, at least, each species can exist in any phase and can transfer between phases via dissolution, evaporation, condensation and so forth, subject to thermodynamic constraints. We shall assume here that the rock is chemically inert and that there are no intraphase or stoichiometric chemical reactions, although in such applications as enhanced oil recovery by alkaline fluid injection reactions of this kind may be important.

In our new formalism, each pair (i, α) , with *i* chosen from the species indices and α chosen from the phases, is a constituent. Thus, for example, CH₄ in the gas phase is one constituent, CH₄ in oil another and *n*-C₄H₁₀ in oil yet another. Each constituent (i, α) has its own *intrinsic mass density* ρ_i^{α} , measured as mass of *i* per unit volume of α , and its own velocity \mathbf{v}_i^{α} . To accommodate the familiar kinematics of phases, we shall still associate with each phase α its volume fraction ϕ_{α} , and if $\phi = 1 - \phi_R$ as before, then we define the saturation of fluid phase α as $S_{\alpha} = \phi_{\alpha}/\phi$. Using these basic quantities, we define the following variables:

$$\rho^{\alpha} = \sum_{i=1}^{N} \rho_{i}^{\alpha} = \text{intrinsic mass density of phase } \alpha$$

 $\omega_i^{\alpha} = \rho_i^{\alpha} / \rho^{\alpha} = \text{mass fraction of species } i \text{ in phase } \alpha$

$$\rho = \phi \sum_{\alpha \neq R} S_{\alpha} \rho^{\alpha} = \text{bulk density of fluids}$$

$$\omega_i = (\phi/\rho) \sum_{\alpha \neq R} S_\alpha \rho^\alpha \omega_i^\alpha$$

...

= total mass fraction of species *i* in the fluids

$$\mathbf{v}^{\alpha} = (1/\rho^{\alpha}) \sum_{i=1}^{N} \rho_{i}^{\alpha} \mathbf{v}_{i}^{\alpha}$$

= barycentric velocity of phase α

$$\mathbf{u}_{i}^{\alpha} = \mathbf{v}_{i}^{\alpha} - \mathbf{v}^{\alpha}$$

= diffusion velocity of species *i* in phase α

If the index N+1 represents the species making up the inert rock phase, then the following constraints hold:

$$\sum_{i=1}^{N} \omega_i = \sum_{i=1}^{N} \omega_i^{\alpha} = \sum_{\alpha} \phi_{\alpha} = \sum_{\alpha \neq R} S_{\alpha} = 1$$

where the index α in the second sum can represent any fluid phase, and

$$\sum_{i=1}^{N} \mathbf{u}_{i}^{\alpha} = \mathbf{0}$$

Each constituent (i, α) has its own mass balance, given by analogy with equation (1) as

$$\frac{\partial}{\partial t} \left(\phi_{\alpha} \rho_{i}^{\alpha} \right) + \nabla \cdot \left(\phi_{\alpha} \rho_{i}^{\alpha} \mathbf{v}_{i}^{\alpha} \right) = r_{i}^{\alpha}$$

where the exchange terms r_i^{α} must obey the restriction $\sum_{i=1}^{N} \sum_{\alpha \neq R} r_i^{\alpha} = 0$. If we impose the further constraint that there are no intraphase chemical reactions, then we have in addition $\sum_{\alpha \neq R} r_i^{\alpha} = 0$ for each species i = 1, ..., N. Since phase velocities are typically more accessible to measurement than species velocities, it is convenient to rewrite the constituent mass balance as

$$\frac{\partial}{\partial t} \left(\phi S_{\alpha} \rho^{\alpha} \omega_{i}^{\alpha} \right) + \nabla \cdot \left(\phi S_{\alpha} \rho^{\alpha} \omega_{i}^{\alpha} \mathbf{v}^{\alpha} \right) + \nabla \cdot \mathbf{j}_{i}^{\alpha} = r_{i}^{\alpha}$$

where $\mathbf{j}_{i}^{\alpha} = \phi S_{\alpha} \rho^{\alpha} \omega_{i}^{\alpha} \mathbf{u}_{i}^{\alpha}$ stands for the *diffusive flux* of constituent (i, α) . Summing this equation over all fluid phases α and using the restrictions gives a total mass balance for each species *i*:

$$\frac{\partial}{\partial t}(\rho\omega_i) + \nabla \cdot \left[\phi(S_w \rho^w \omega_i^w \mathbf{v}^w + S_o \rho^o \omega_i^o \mathbf{v}^o + S_G \rho^G \omega_i^G \mathbf{v}^G)\right] + \nabla \cdot (\mathbf{j}_i^w + \mathbf{j}_i^o + \mathbf{j}_i^G) = 0 \qquad i = 1, \dots, N$$

To establish flow equations for each species, we need velocity field equations for each fluid phase and some constitutive equations for the diffusive fluxes \mathbf{j}_{i}^{α} . For the fluid velocities we may postulate Darcy's law, equation (4), assuming in addition that the porous medium is isotropic. For the diffusive fluxes the appropriate assumption is not so clear. In single-phase flows through porous media, the diffusive flux of a species with respect to the fluid's barycentric velocity is called hydrodynamic dispersion. As reviewed in Section 5, theories of hydrodynamic dispersion in multiphase flows remain poorly developed. The most common approach in oil reservoir simulation is to assume that hydrodynamic dispersion is a small enough effect that the diffusive fluxes in the mass balance for each species are negligible. Thus we arrive at the flow equation for species *i* in the fluids:

$$\frac{\partial}{\partial t} \left[\phi(S_{W} \rho^{W} \omega_{i}^{W} + S_{O} \rho^{O} \omega_{i}^{O} + S_{G} \rho^{G} \omega_{i}^{G}) \right] - \nabla \cdot \left[\frac{k k_{rW} \rho^{W} \omega_{i}^{W}}{\mu_{W}} (\nabla p_{W} - \rho^{W} g \nabla Z) + \frac{k k_{rO} \rho^{O} \omega_{i}^{O}}{\mu_{O}} (\nabla p_{O} - \rho^{O} g \nabla Z) \right. \\ \left. + \frac{k k_{rG} \rho^{G} \omega_{i}^{G}}{\mu_{G}} (\nabla p_{G} - \rho^{G} g \nabla Z) \right] = 0 \qquad i = 1, \dots, N$$

To close this set of equations, we need some supplementary constraints giving relationships among the variables. One class of supplementary constraints consists of the thermodynamic relationships giving phase densities and compositions as functions of pressure and overall fluid mixture composition. Conceptually, these relationships take the forms

$$\rho^{\alpha} = \rho^{\alpha}(\omega_1^{\alpha}, \ldots, \omega_{N-1}^{\alpha}, p_{\alpha}) \qquad \alpha = W, O, G \quad i = 1, \ldots, N-1$$

$$\omega_i^{\alpha} = \omega_i^{\alpha}(\omega_1, \dots, \omega_{N-1}, \rho_{\alpha}) \qquad \alpha = W, O, G$$

$$S_{\alpha} = S_{\alpha}(\omega_1, \dots, \omega_{N-1}, p_{\alpha}) \qquad \alpha = W, O, G$$

However, it is important from a computational viewpoint to observe that the actual mathematical statements of these relationships may constitute simultaneous sets of nonlinear algebraic equations giving phase densities, compositions and saturations implicitly. This occurs, for example, when one uses equal-fugacity constraints in conjunction with an equation of state to solve for local thermodynamic equilibria, as discussed further below.

The other class of supplementary constraints includes constitutive relationships for the particular rock-fluid system being modelled. These relationships may take the following forms:

$$p_{COW} = p_{COW}(S_O, S_G) \qquad \alpha = W, O, G$$
$$p_{CGO} = p_{CGO}(S_O, S_G)$$
$$k_{r\alpha} = k_{r\alpha}(S_O, S_G)$$

Here, as mentioned in Section 2, we have greatly simplified the physics of many compositional flows by omitting possible dependencies on fluid composition through variations in interfacial tension.

4.2 Black-oil simulation

Black-oil models are special cases of the general compositional equations that allow limited interphase mass transfer, the composition of each phase depending on pressures only. This class of models has become a standard engineering tool in the petroleum industry. As a consequence the literature on the numerics of black-oil simulation, which apparently begain in 1948 with a consulting report by John van Neumann¹⁵⁶, has become quite extensive. Indeed, there are now several books in print devoted to black-oil simulation^{114,18}. Since any attempt to cover this field in an article of the present scope would be futile, we shall merely review the formulation of the black-oil equations and discuss selected aspects of their numerical solution.

The fundamental premise of the black-oil model is that a highly simplified, three-species system can often serve as an adequate model of the complex mixtures of brine and hydrocarbons found in natural petroleum reservoirs. For practical purposes, petroleum engineers define these three pseudo-species according to what appears at the surface, at stock-tank conditions (STC), after production of the reservoir fluids. Thus, we have the species o, which is stock-tank water. Underground, at reservoir conditions (RC), these species may partition themselves among the three fluid phases O, G and W in a distribution depending on the pressures in the formation.

Now we impose a set of thermodynamic constraints on this partitioning of species. First, we assume that there is no exchange of water w into the nonaqueous phases O and G, so that $\omega_w^w = 1$, and $\omega_w^o = \omega_w^o = 0$. Second, we allow no exchange of oil o into the vapour phase G or the aqueous liquid W, so that $w_o^o = 1$, and $\omega_o^w = \omega_o^c = 0$. Third, we prohibit the dissolution of gas g into the aqueous liquid W, so that $\omega_g^W = 0$. However, we allow the gas g to dissolve in the hydrocarbon liquid O according to a pressure-dependent relationship called the solution gas-oil ratio, defined by

$$R_s(p_o) = \frac{\text{volume of } g \text{ in solution at } RC}{\text{volume of } o}$$

where the volumes refer to volumes at STC.

To facilitate further reference to volumes of species at STC, we relate the phase densities ρ^{α} at RC to the species densities ρ_i^{STC} at STC by defining the *formation volume factors*. For W and G these definitions are fairly simple:

$$B_W(p_W) = \rho_W^{\text{STC}} / \rho^W \qquad B_G(p_W) = \rho_g^{\text{STC}} / \rho^G$$

For the hydrocarbon liquid O, however, we must also account for the mass of dissolved gas at RC:

$$B_o(p_o) = (\rho_o^{\text{STC}} + R_S \rho_a^{\text{STC}})/\rho^c$$

If we substitute these definitions into the flow equations (16) for the species o, g, w and divide through by the constants ρ_i^{STC} , we obtain the three black-oil equations

$$\frac{\partial}{\partial t} \left(\frac{\phi S_W}{B_W} \right) - \nabla \cdot \left[\lambda_W (\nabla p_W - \gamma_W \nabla Z) \right] = 0$$
(17a)

$$\frac{\partial}{\partial t} \left(\frac{\phi S_o}{B_o} \right) - \nabla \cdot \left[\lambda_o (\nabla p_o - \gamma_o \nabla Z) \right] = 0$$
(17b)

$$\frac{\partial}{\partial t} \left[\phi \left(\frac{S_G}{B_G} + \frac{R_S S_O}{B_O} \right) \right] - \nabla \cdot \left[\lambda_G (\nabla p_G - \gamma_G \nabla Z) \right] \\ - \nabla \cdot \left[R_S \lambda_O (\nabla p_O - \gamma_O \nabla Z) \right] = 0 \quad (17c)$$

where $\lambda_{\alpha} = \Lambda_{\alpha} / B_{\alpha}$ and $\gamma_{\alpha} = \rho^{\alpha} g$.

These equations constitute a system of coupled, nonlinear, time-dependent partial differential equations. Each of the equations is formally parabolic in appearance. However, as suggested by the greatly simplified development in Section 3.3, the system can exhibit behaviour more typical of hyperbolic equations if capillary influences are small. To see this, consider the two-phase version of equation (17) in which gas is absent, porosity is constant and fluid compressibilities and gravity forces have no effect. The flow equations in this case reduce to

$$-\phi \frac{\partial S_{w}}{\partial t} = \nabla \cdot (\lambda_{o} \nabla p_{o})$$
$$\phi \frac{\partial S_{w}}{\partial t} = \nabla \cdot (\lambda_{w} \nabla p_{w})$$

Adding these two equations gives a total flow equation $\nabla \cdot \mathbf{q} = 0$, where $\mathbf{q} = -\lambda_o \nabla p_o - \lambda_W \nabla p_W$. Calling $\lambda = \lambda_o + \lambda_W$ and $p = (p_o + p_W)/2$, we can rewrite the total flow equation as

$$\nabla \cdot (\lambda \nabla p) - \left(\frac{\lambda_W - \lambda_O}{2}\right) \nabla p_{COW} = 0$$

If we examine the case when $\nabla p_{COW} \simeq 0$, the total flow equation reduces to an elliptic pressure equation

$$\nabla \cdot (\lambda \nabla p) = 0 \tag{18a}$$

Then, recalling the fractional flow function $f_W = \lambda_W / (\lambda_O + \lambda_W)$, we can rewrite the water flow equation as

$$\phi \, \frac{\partial S_W}{\partial t} + \mathbf{q} \cdot \nabla f_W(S_W) = 0 \tag{18b}$$

This saturation equation is the hyperbolic analog of the one-dimensional Buckley-Leverett problem.

Several approaches to solving the general system (17) numerically have appeared in the petroleum engineering

literature. We shall review two of the most popular methods: the simultaneous solution (SS) method and the implicit pressure-explicit saturation (IMPES) method.

The SS method, introduced by Douglas, Peaceman and Rachford⁵⁹, and further developed by Coats *et al.*⁴⁵, treats the flow equations (17) as simultaneous equations for the fluid pressures p_0 , p_G and p_W . Inverting the capillarity relationships and imposing the restriction on fluid saturations then yields the saturations S_0 , S_G and S_W . For ease of presentation, let us examine the two-phase case, assuming that the vapor phase G does not appear and that the porosity ϕ is constant.

The first step in the formulation is to rewrite the flow equations so that the pressures p_0 and p_w appear as explicit unknowns. To do this, we apply the chain rule to the accumulation terms, giving

$$\frac{\partial}{\partial t} \left(\frac{\phi S_{W}}{B_{W}} \right) = \phi S_{W} b_{W} \frac{\partial p_{W}}{\partial t} + \frac{\phi S'_{W}}{B_{W}} \left(\frac{\partial p_{O}}{\partial t} - \frac{\partial p_{W}}{\partial t} \right)$$
$$\frac{\partial}{\partial t} \left(\frac{\phi S_{O}}{B_{O}} \right) = \phi S_{O} b_{O} \frac{\partial p_{O}}{\partial t} - \frac{\phi S'_{W}}{B_{O}} \left(\frac{\partial p_{O}}{\partial t} - \frac{\partial p_{W}}{\partial t} \right)$$

where $b_{\alpha} = d(1/B_{\alpha})/dp_{\alpha}$ and S'_{W} signifies the derivative of the inverted capillarity relationship $S_{W}(p_{COW})$. This device allows us to write the system (17) as follows:

$$\phi \begin{bmatrix} (S_{W}b_{W} - S'_{W}/B_{W}) & (S'_{W}/B_{O}) \\ (S'_{W}/B_{O} & (S_{O}b_{O} - S'_{W}/B_{O}) \end{bmatrix} \frac{\partial}{\partial t} \begin{bmatrix} p_{W} \\ p_{O} \end{bmatrix} \\ -\nabla \cdot \begin{bmatrix} (\Lambda_{W}/B_{W})\nabla & 0 \\ 0 & (\Lambda_{O}/B_{O})\nabla \end{bmatrix} \begin{bmatrix} p_{W} \\ p_{O} \end{bmatrix} \\ + \begin{bmatrix} \rho^{W}g\nabla Z \\ \rho^{o}g\nabla Z \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$
(18)

Now we can employ some finite-difference or finite element method to approximate the spatial derivative in equation (18), getting a system of evolution equations having the form

$$[M] \frac{d}{dt} \{p\} + [K] \{p\} = \{f\}$$

Here [M] is the mass matrix, [K] is the stiffness matrix, $\{p\}$ represents the vector of unknown nodal values of oil and water pressure and $\{f\}$ is a vector containing information from the discretized boundary conditions. Since the entries of [M] and [K] vary with the unknown pressures, this system is nonlinear. Therefore the timestepping approximation must be iterative. As an example, we might use a Newton-like procedure analogous to that presented in Section 3.1, yielding

$$\left(\frac{1}{\Delta t} [M]^{n+1,m} + [K]^{n+1,m}\right) \{\delta p\}^{n+1,m+1}$$

= $-\left[\frac{1}{\Delta t} [M]^{n+1,m} (\{p\}^{n+1,m} - \{p\}^n) - [K]^{n+1,m} \{p\}^{n+1,m} + \{f\}^{n+1,m}\right] = -\{R\}^{n+1,m}$

In this scheme the notation $\{R\}^{n+1,m}$ suggests that we regard the right side as a residual, iterating at each time step until $\|\{R\}^{n+1,m}\|$ is small enough in some norm.

The formulation presented above is not unique. In fact,

several variants of the SS method have appeared, including formulations treating different sets of variables as principal unknowns. Aziz and Settari¹⁸ provide a survey of these alternative approaches.

In the IMPES formulation, the basic idea is to combine the flow equations (17) to get an equation for one of the fluid pressures³². Solving the equation implicitly provides the information necessary to update the saturations explicitly at each time step, using an independent set of flow equations and the restriction that saturations sum to unity. Sheldon, Zondek and Cardwell¹⁴¹ and Stone and Garder¹⁴⁵ introduced this method.

The development follows a line of reasoning paralleling that leading to equations (18). We begin, as in the SS method, by expanding the accumulation terms, this time leaving saturations and pressures as principal unknowns. For the three-phase system, this leads to the following finite-difference approximations

$$\phi \frac{\partial}{\partial t} \left(\frac{S_W}{B_W} \right) = \frac{1}{\Delta t} \left(C_1 \Delta_t S_W + C_2 \Delta_t p_W \right) + \mathcal{O}(\Delta t)$$
$$\phi \frac{\partial}{\partial t} \left(\frac{S_O}{B_O} \right) = \frac{1}{\Delta t} \left(C_3 \Delta_t S_O + C_4 \Delta_t p_O \right) + \mathcal{O}(\Delta t)$$
$$\phi \frac{\partial}{\partial t} \left(\frac{S_G}{B_G} + \frac{R_S S_O}{B_O} \right)$$
$$= \frac{1}{\Delta t} \left(C_5 \Delta_t S_G + C_6 \Delta_t p_G + C_7 \Delta_t S_O + C_8 \Delta_t p_O \right) + \mathcal{O}(\Delta t)$$

The coefficients $C_1, ..., C_8$ appearing here stand for the appropriate derivatives extracted using the chain rule, and $\Delta_t u = u^{n+1} - u^n$ defines the time-difference operator.

The next step involves the crucial assumption that the capillary pressures p_{COW} , p_{CGO} change negligibly over a time step. This assumption implies that $\Delta_t p_O = \Delta_t p_W = \Delta_t p_G$ and, furthermore, that we can treat the capillary contributions to the flux terms explicitly. Thus, our implicit, temporally discrete approximations to equation (17) become

$$C_1 \Delta_t S_W + C_2 \Delta_t p_o = \Delta t \nabla \cdot \left[\lambda_W^{n+1} (\nabla p_o^{n+1} - \nabla p_{COW}^n - \gamma_W^{n+1} \nabla Z) \right]$$
(19a)

$$C_3\Delta_t S_0 + C_4\Delta_t p_0 = \Delta t \nabla \cdot \left[\lambda_0^{n+1} (\nabla p_0^{n+1} - \gamma_0^{n+1} \nabla Z)\right] \quad (19b)$$

$$C_{5}\Delta_{t}S_{G} + C_{7}\Delta_{t}S_{O} + (C_{6} + C_{8})\Delta_{t}p_{O}$$

= $\Delta t \nabla \cdot [\lambda_{G}^{n+1}(\nabla p_{O}^{n+1} + \nabla p_{CGO}^{n+1} - \gamma_{G}^{n+1}\nabla Z)$
+ $R_{S}^{n+1}\lambda_{O}^{n+1}(\nabla p_{O} - \gamma_{O}^{n+1}\nabla Z)]$ (19c)

To get a single pressure equation from this set, we multiply equation (19c) by the coefficient $B = C_3/(C_7 - C_5)$, multiply equation (19a) by $A = BC_5/C_1$, add equations (19a-c), and observe that the saturation differences in the accumulation terms now sum to an expression proportional to $\Delta_t(S_W + S_O + S_G) = 0$. Therefore our weighted sum of the time-differenced flow equations yields

$$C^{n+1}\Delta_{t}p_{O} = \Delta t \{ A^{n+1}\nabla \cdot (\lambda_{W}^{n+1}\nabla p_{O}^{n+1}) + \nabla \cdot (\lambda_{O}^{n+1}\nabla p_{O}^{n+1}) + B^{n+1}\nabla \cdot [(\lambda_{G}^{n+1} + R_{S}^{n+1}\lambda_{O}^{n+1})\nabla p_{O}^{n+1}] - \Gamma^{n+1} \}$$
(20)

The new parameter Γ is shorthand for the weighted sum of the gravity terms, and $C = AC_2 + C_4 + B(C_6 + C_8)$. Equation (20) is the pressure equation.

Now, provided we have an appropriate technique for producing discrete approximations to the spatial derivatives appearing in these equations, we can implement the following time-stepping procedure.

- (i) Solve equation (20) implicitly, using some iterative scheme.
- Solve equation (19a) explicitly for $\Delta_{i}S_{W}$ and update (ii) the water saturation; solve (19b) for ΔS_0 and update the oil saturation, setting $S_G^{n+1} = 1 - S_W^{n+1} - S_O^{n+1}$. Compute p_{COW}^{n+1} and p_{CGO}^{n+1} using the new saturations;
- (iii) then use these to update p_W and p_G .
- Begin the next time step. (iv)

Notice that, in contrast to the SS formulation, the IMPES approach requires the implicit solution of only one flow equation at each time step. As with the SS methods, variants on this development have appeared; see Aziz and Settari¹⁸ for a survey.

The IMPES approach offers the obvious advantage that, with only one implicit equation to solve per time step, the algorithm requires smaller matrix inversions at each iteration. The resulting computational savings can be significant in problems involving large numbers of grid points. On the other hand, because it treats capillary pressures explicitly, the IMPES method suffers instability when the time step Δt exceeds a critical value. This limitation can be inconvenient if the critical value of Δt is unknown or small compared with the life of a field project. The SS method, while requiring more computation per time step, boasts greater stability. This can prove to be a decided advantage when the problem to be solved exhibits strongly nonlinear phenomena, such as coning near wellbores or liquid hydrocarbons passing through bubble points.

The performance of black-oil models is quite sensitive to the treatment of nonlinear coefficients in the discrete flow equations. Consider, for example, the spatial treatment of the flux coefficients λ_{α} . It is standard practice to use upstream-weighted approximations to these coefficients. To see why, examine the results of Fig. 7, showing predictions of a one-dimensional black-oil model using several midpoint and upstream approximations to λ_{x} . These plots show that upstream-biased analogs of the flux coefficients force the numerical solution to converge to the correct physical solution when capillarity is small. This result corroborates our discussion of the Buckley-Leverett problem in Section 3.3, since, as we have argued, the black-oil system exhibits similar hyperbolic features.

The temporal weighting of the flux coefficients also affects the solution to the black-oil equations. It is a fairly common practice to treat these coefficients explicitly. As Settari and Aziz show, however, this tactic leads to limits on time steps allowable for stable solutions. The limitation is especially severe in problems with gas percolation, which occurs when the fluid mixture pressure drops below the bubble point. Blair and Weinaug²⁸ introduce the implicit treatment of the flux coefficients that alleviates this stability problem. As Coats⁴³ reviews, this highly stable method has proved attractive in simulating other, more complex oil-reservoir flows.

One of the most important problems in black-oil simulation, and in fact in reservoir simulation more generally, is the computational inefficiency associated with the solution of large systems of linear algebraic equations. In either the SS or the IMPES approach, the



Fig. 7. Black-oil model solutions using (a) midpointweighted flux coefficients and (b) upstream-weighted flux coefficients18

iterative time-stepping scheme calls for the solution of matrix equations at each iteration of each time step. For simulations at practical scales these calculations alone can tax the storage and CPU-time resources of the largest machines currently available. A great deal of recent research has focused on the development of fast iterative techniques for the solution of the large matrix systems arising in applications.

Among the oldest of these iterative techniques are the block-iterative methods. These methods use the blocked, sparse structure of the linear systems to solve the equations iteratively, block-by-block²⁷. Block iterative methods, such as block-successive overrelaxation, tend to be quite sensitive to 'tunable' iteration parameters such as overrelaxation coefficients.

Another fairly old class of iterative techniques consists of alternating direction methods. These methods, introduced in the context of finite differences by Peaceman and Rachford¹¹⁵, Douglas and Rachford⁶⁰ and Douglas⁵⁶, reduce the computational effort in multidimensional problems by implicitly solving over one space dimension at a time. While interest in alternating direction techniques for finite differences has waned in recent years, interest in alternating-direction Galerkin and collocation methods has been growing; see, for example, Ewing⁶² and Celia and Pinder³⁶.

In a different approach, Stone¹⁴³ proposes the strongly implicit procedure (SIP) for solving matrix equations implicitly. The idea here is to replace a matrix equation

having the form $[A]\{p\} = -\{R\}$ by an iterative scheme having the form

$$([A] + [N]) \{p\}^{m+1} = ([A] + [N]) \{p\}^m - ([A] \{p\}^m + \{R\})$$

By properly choosing the matrix [N], one can efficiently factor ([A] + [N]) into a product of sparse upper- and lower-triangular matrices. This idea gives rise to an algorithm that gives relatively rapid convergence to the solution $\{p\}$ of the original equation.

Finally, much recent interest has focused on *conjugate* gradient methods for solving large matrix equations. These methods have their theoretical roots in the equivalence between linear systems and minimization problems for positive self-adjoint matrices⁹⁵. However, the methods admit extensions to the nonself-adjoint operators that arise in fluid flow problems, especially in conjunction with such preconditioning methods as incomplete LU factorization and nested factorization^{15,110, 115,122}. The motivation for preconditioning is that, for parabolic flow equations, fine spatial grids can yield iteration equations $[A]\{p\} = -\{R\}$ in which the condition number of [A] is large. By 'preconditioning' [A] with another matrix $[A^*]^{-1}$, one can arrive at an equivalent system

$$[A^*]^{-1}[A]\{p\} = -[A^*]^{-1}\{R\}$$

that is better conditioned. Clever choices of $[A^*]^{-1}$ ensure that $[A^*]^{-1}\{R\}$ will be easy to compute at each iteration, thus promoting computational efficiency. It is reasonable to expect that preconditioned conjugategradient methods will play a larger role in oil reservoir simulation as the technology continues to advance.

4.3 Compositional simulation

The most ambitious applications of the equations for compositional flows arise in the simulation of enhanced oil recovery processes. Many of these processes depend for their success on the effects of interphase mass transfer on fluid flow properties. One noteworthy example of such a process is miscible gas flooding. This technology consists of injecting an originally immiscible gas, such as CO_2 , into an oil reservoir with the aim of developing a miscible displacement front in situ. In successful projects, miscibility develops through continuous interphase mass transfers, leading the fluid mixture toward its critical composition and hence reducing the interfacial tension between the resident oil and the displacing fluid. Compositional modelling serves as an important tool in other oil recovery problems, too, including production from gas condensate reservoirs and recovery of volatile oils.

There are several ways to classify compositional simulators. One way is to characterize the models according to their treatment of fluid-phase thermodynamics. There are at least two forms in which the thermodynamic constraints mentioned in Section 4.1 can appear. The oldest form consists of tabular data for the equilibrium ratios ω_i^G/ω_i^O of species mass (or mole) fractions in the vapour and liquid hydrocarbon phases. Thus, given overall hydrocarbon pressures and compositions at a point in the reservoir, one can compute fluid saturations, densities and compositions by performing 'flash' calculations familiar to chemical engineers¹⁰⁹. The other form of the thermodynamic constraints is the requirement that vapour and liquid fugacities be equal for each component: $f_i^G = f_i^O$, i = 1, ..., N. This approach is especially attractive when used in conjunction with an

equation of state such as that proposed by Peng and Robinson¹¹⁷. Equation-of-state methods have the advantage of thermodynamic consistency near fluid critical points, leading to calculations with better convergence properties in models of miscible gas floods. In either the equilibrium-ratio approach or the equationof-state approach, though, the thermodynamic constraints amount to a system of nonlinear algebraic equations giving fluid saturations, densities and compositions implicitly.

Another way to classify compositional models is according to the manner in which they solve the flow equations (16). Two general schemes have appeared. One of these treats the flow equations sequentially, solving an overall pressure equation and then updating the remaining N-1 composition equations and the thermodynamic constraints at each time step or iteration. This approach parallels the IMPES method in black-oil simulation, and, as one might expect, it offers computational speed at the expense of some stability. The other scheme solves the entire system of flow equations and thermodynamic constraints simultaneously at each time step. This approach, analogous to the SS method of Section 4.2, leads to enormous matrix equations at each iteration. However, it enjoys a greater stability than the sequential schemes. Given adequate computers, this *fully* implicit approach is quite attractive, since the compositional equations can exhibit behaviour that is too complex to permit a priori estimates of stability constraints.

Among the simulators using sequential methods are those advanced by Roebuck *et al.*¹³⁰; Nolen¹⁰⁹; Van Quy, Corteville and Simandoux¹⁵³; Kazemi, Vestal and Shank⁸⁸; Nghiem, Fong and Aziz¹⁰⁸; Watts¹⁵⁸ and Allen^{6,7}. Let us examine the time-stepping structure of one such model⁷, restricting attention to an oil-gas system in which gravity has no effect. Summing the flow equations over all N species gives an overall fluid mass balance

$$\frac{\partial \rho}{\partial t} = \nabla \cdot (T_T \nabla p_G - T_O \nabla p_{CGO}) \tag{21}$$

where $T_{\alpha} = k k_{r\alpha} \rho^{\alpha} / \mu_{\alpha}$ for each fluid α and $T_T = T_G + T_O$. This leaves N - 1 independent species balances

$$\frac{\partial(\rho\omega_i)}{\partial t} = \nabla \cdot (\Upsilon_i \nabla p_G - T_O \omega_i^O \nabla p_{CGO}) \quad i = 1, \dots, N - 1$$
(22)

where $\Upsilon_i = T_G \omega_i^G + T_O \omega_i^O$. We can regard equation (21) as an equation for the pressure p_G , using equation (22) to solve for the overall species mass fractions ω_i . The thermodynamic constraints then give the saturation, densities and compositions of the liquid and vapour phases.

To solve these equations sequentially, we first discretize the pressure equation (21) in time, using the following Newton-like iterative scheme:

$$\rho^{n+1,m} + \left(\frac{\partial \rho}{\partial p_G}\right)^{n+1,m} \delta p_G^{n+1,m+1} - \rho^n = \Delta t \nabla \cdot [T_T^{n+1,m} \nabla (p_G^{n+1,m} + \delta p_G^{n+1,m+1}) - T_O^{n+1,m} \nabla p_{CGO}^{n+1,m}]$$
(23)

This scheme is similar to that used in the unsaturated flow

equation of Section 3.1. After solving for $\delta p_G^{n+1,m+1}$, we update the pressure iterate by setting $p_G^{n+1,m+1} = p_G^{n+1,m} + \delta p_G^{n+1,m+1}$. Then we can update each mass fraction $\omega_1, \ldots, \omega_{N-1}$ using the finite difference approximation

$$\Delta_{t}\omega_{i}^{n+1,m+1} = \frac{1}{\rho^{n+1,m+1}} \left\{ \Delta t \nabla \cdot \left[\Upsilon_{i}^{n+1,m} \nabla p_{G}^{n+1,m+1} - (T_{O}\omega_{i}^{O})^{n+1,m} \nabla p_{CGO}^{n+1,m} \right] - \omega_{i}^{n} \Delta_{t} p^{n+1,m+1} \right\}$$
(24)

to equation (22), setting $\omega_i^{n+1,m+1} = \omega_i^n + \Delta_t \omega_i^{n+1,m+1}$. This update calls for values of $\rho^{n+1,m+1}$, which are available from the latest iteration of equation (23) as

$$\rho^{n+1,m+1} = \Delta t \nabla \cdot (T_T^{n+1,m+1} \nabla p_G^{n+1,m+1} - T_O^{n+1,m} \nabla p_{CGO}^{n+1,m}) + \rho$$

This iterative sequence requires the solution of a matrix equation only in the spatially discrete analog of equation (23), since equation (24) has an 'explicit' form at each iteration. Notice that, while the scheme is not fully implicit, it calls for implicit treatment of the flux coefficients, which lends to the stability of the formulation. Figure 8 shows a flow chart for the time-stepping algorithm, and Fig. 9 shows a profile of vapour-liquid interfacial tensions in a simulated vaporizing gas drive⁷. The wave of decreasing tensions indicates the development of a zone in which the fluid displacement is very nearly miscible.

With the advent of large, fast digital computers, interest has grown in the fully implicit approach to compositional simulation. Among the models based on this approach are those reported by Fussell and Russell⁷², Coats⁴², Heinemann⁸⁰, and Chien, Lee and Chen³⁸. This class of formulations treats the discretized flow equations and thermodynamic constraints as a set of simultaneous



Fig. 8. Flow chart of time-stepping procedure for a sequential compositional simulator⁷



Fig. 9. Interfacial tension profile at various times for a compositional simulation of a vaporizing gas drive⁷

nonlinear algebraic equations, generally using some Newton-like iterative scheme to advance between time steps. The implicit nature of the formulations leads to great stability at the expense of solving large matrix equations of the form $[A]\{y\} = -\{R\}$ at each iteration. Moreover, the iteration matrix [A] typically has less sparseness than the matrices arising from sequential schemes, since simultaneous schemes account for more of the nonlinear coupling between variables. Young and Stephenson¹⁶⁵ present one approach to mitigating this complication by evaluating the flux coefficients explicitly. As should be expected, this scheme reduces the computational effort of the fully implicit approach while sacrificing some of its stability.

There are several areas of difficulty common to practically all compositional simulators. One class of problems concerns the mathematical representation of fluid phase behaviour. Most research in compositional simulation now focuses on methods using cubic equations of state coupled with equal-fugacity constraints to represent the fluid thermodynamics. While this approach guarantees thermodynamic consistency and therefore ensures smooth behaviour of fluid densities, it requires the solution of highly nonlinear algebraic equations in addition to the discretized flow equations. Furthermore, the numerical solution of these thermodynamic constraints often suffers poor convergence when fluid pressures and compositions approach critical points¹²⁹. While the numerical problems associated with fluid phase behaviour calculations pose serious challenges to the petroleum industry, an extensive discussion of research in this area would carry us far afield.

Another problem affecting compositional simulation is the numerical smearing introduced by upstream weighting. While this source of error affects other numerical models using upstream weighting, it is particularly problematic in compositional simulation. Because compositional models require so much storage and CPU time per spatial node, field-scale simulations often must use relatively few nodes and correspondingly coarser grids. The artifical diffusion that results can introduce large errors in species mass fractions and thus lead to unreal thermodynamics.

Several investigators have proposed methods for alleviating numerical diffusion in compositional simulators. Chase³⁷, for example, proposes local grid refinement methods for use with Galerkin finite elements. Section 6.4 discusses local grid refinement in more detail. Wilson, Tan and Casinader¹⁶⁰ advance a method for selecting upstream-weighted difference approximations that yield reduced artificial smearing. Ewing and Heinemann^{64,65} discuss the use of mixed finite-element methods to reduce smearing in compositional models. These authors propose that inaccurate fluid velocities, obtained by numerically differentiating pressure fields, aggravate numerical smearing. By incorporating mixed methods into their numerical scheme, they compute more accurate velocities and thereby help preserve sharp composition fronts in the numerical solution. Section 6 discusses mixed finite-element methods more thoroughly.

Finally, the growing appeal of the fully implicit approach implies that the computational effort associated with the inversion of large linear systems will become an increasingly important concern. The stakes involved in the linear algebra of compositional modelling are much higher than in black-oil simulation, since a typically fully implicit compositional model must solve the discretized flow equations and equal-fugacity constraints for between seven and ten species. This avenue of research should be active for quite some time to come.

5. OUTSTANDING PROBLEMS: PHYSICS

The next two sections review some of the outstanding problems in simulating multiphase flows in porous media. Roughly speaking, these problems fall into two categories: difficulties arising because our knowledge of the physics of multiphase flows is incomplete and difficulties in devising mathematical methods to capture known physics. The two categories are not as distinct as this description suggests. For some phenomena our lack of physical understanding hinders attempts to model them mathematically. Viscous fingering is an example, as discussed below. For other phenomena, the mathematical difficulties are evidence of physical complications that lead to peculiar behaviour in the governing equations. The occurrence of sharp fronts in immiscible flows is an example of this coupling. Nevertheless, the distinction between physical and numerical difficulties makes some sense if we interpret it as suggesting strategies for future research. In this section we consider several physical problems.

5.1 Viscous fingering

Often, in two-phase flows, the bulk of one fluid lies upstream of the other. In this case we say that the 'upstream' phase displaces the 'downstream' phase, even though there may be large regions where both phases flow simultaneously. The global behaviour of such flows depends strongly on whether the mobility of the displacing fluid is greater or less than that of the displaced fluid. In the latter case, when the *mobility* ratio $\Lambda_{displacing}$ $\Lambda_{\text{displaced}} = M < 1$, the flow proceeds stably. This implies that velocity fields and saturations depend continuously on the boundary and initial conditions and well rates. When M > 1, however, channels of high displacing-fluid saturation can bypass zones of displaced fluid in a geometrically irregular pattern. These irregularities in the fluid displacement reflect the instability of immiscible displacements at high mobility ratios. The channeling phenomenon is called viscous fingering. While this phenomenon occurs in both single-phase and multiphase flows, we shall restrict our attention to the multiphase case.

Viscous fingering is economically important in oil reservoir engineering, where displacement of oil by some injected fluid is common to almost all recovery processes past primary production. In many cases the injected fluid is water, a gas such as CO_2 or N_2 , or a surfactant solution. These fluids tend to be more mobile than common crude oils; therefore viscous fingering can occur. As a result, such a displacement scheme may sweep only a small fraction of the oil-bearing rock between an injection well and a production well. This inefficiency motivates reservoir engineers to add mobility control agents, such as hydrolysed polymers, to injected fluids to lower their mobility.

Investigations into the physics of viscous fingering in immiscible displacements began in the late 1950s. Saffman and Taylor¹³² investigated an analogy between porousmedium flows and Hele-Shaw flows, confirming that M > 1 leads to frontal instability. Chuoke, van Meurs and van der Pol⁴¹ applied perturbation techniques to show the existence of a critical wavelength for unstable fingers. From these early papers through the 1970s the literature on viscous fingering mushroomed. Ewing and George⁶³ provide a fairly extensive review of this body of work.

Research into viscous fingering has continued in recent years^{76,118,163,94,87}. While controversy still exists, there seems to be broad agreement that unstable fingers are triggered by heterogeneities in the porous medium observable at the microscopic scale. However, the macroscopic governing equations based on Darcy's law do not explicitly account for microscopic heterogeneities. Mathematical models based on the macroscopic equations and assuming a macroscopically homogeneous porous medium therefore have no mechanism for initiating fingers. Consequently, the homogeneous model will not exhibit instability, even though it is present in nature. One might, as an analogy, consider the mathematical model of an ideal pendulum hung vertically upward with zero velocity. The idealised model predicts that the pendulum is at equilibrium, whereas a natural pendulum in such a configuration is unlikely to stay there.

This failure to capture microscopic physics has unfortunate implications in numerical simulation. The response of a mathematical method to unstable immiscible displacements depends on the degree of heterogeneity in the data of the problem. Discrete models can represent spatial heterogeneity only within the limits imposed by the fineness of the spatial grid. Hence, models of immiscible displacement in media exhibiting heterogeneity at many scales can produce qualitatively different results depending on the spatial discretization used.

Several articles have appeared reporting efforts to produce better numerical representations of viscous fingering, given the inherent limitations of discrete methods. Among these are papers by Glimm, Marchesin and McBryan⁷⁸, who propose the random choice method for solving the flow equations, and Ewing, Russell and Wheeler⁶⁶, who examine a mixed method in conjunction with a modified method of characteristics to give accurate approximations of fluid interfaces. Another set of approaches has been to incorporate the 'average' effects of fingering on the mixing of fluids in numerical simulators. This line of research began with Koval⁸⁹ and became a common simulation tool with the introduction of a mixing model by Todd and Longstaff¹⁴⁸. This 'averaging' approach, while currently lacking in rigour, may offer fertile ground for the interaction of sound physical reasoning with the development of numerical techniques.

Finally, there is a great need for more empirical work on viscous fingering. Among the many sources of uncertainty regarding the nature of fingering is the paucity of field-scale data characterizing its effects. As Settari, Price and Dupont¹³⁸ asserts

The study of unstable displacements, particularly viscous fingering, is distingyished by the fact that in no other area of reservoir engineering is there less agreement. There is not even complete agreement on the existence of viscous fingering as a real phenomenon for reservoir conditions, let alone agreement as to the magnitude and interaction of the various mechanisms involved.

5.2 Multiphase hydrodynamic dispersion

As the derivation of the compositional equations in Section 4.1 demonstrates, individual species within a fluid phase need not move with the barycentric velocity of the phase. In porous-media flows, the deviation of species motions with respect to the mean flow of the fluid is called hydrodynamic dispersion. This diffusion-like phenomenon is familiar in the context of single-phase flows such as miscible displacement in petroleum engineering or soluble contaminant transport in groundwater hydrology. However, the literature on hydrodynamic dispersion in multiphase flows is frustratingly sparse.

One likely reason for this sparseness is the difficulty of understanding the physics of hydrodynamic dispersion even in single-fluid flows. Dispersion in porous media actually comprises a set of phenomena, including the following⁷¹:

- molecular diffusion, which to macroscopic observers appears retarded owing to the tortuosity of the solid matrix;
- (ii) Taylor diffusion¹⁴⁶, an effect whereby no-slip boundary conditions at the solid walls cause solutes in small-diameter pore channels to spread with respect to their mean motion;

- (iii) stream splitting, in which parcels of solute-bearing fluid divide at pore-channel intersections, and
- (iv) transit-time deviations, in which the dissimilar tortuosities of adjacent flow paths cause nearby fluid parcels to have different net velocities in the mean flow direction.

Notice that the descriptions of these phenomena belong to the microscopic level of observation, and hence the use of hydrodynamic dispersion to account for their macroscopic effects imposes an inherent loss of information. To modelers, this smearing of small-scale heterogeneities has undesirable implications. Indeed, in models of solute transport in porous media, hydrodynamic dispersion is often the most poorly quantified of all physical parameters fed into the simulator.

Relatively few investigators have ventured to propose quantitative forms for hydrodynamic dispersion in the multiphase setting. Among the earliest laboratory studies of multiphase hydrodynamic dispersion is that of Thomas, Countryman and Fatt¹⁴⁷. These authors find that, when two phases flow in a porous medium, each fluid alters the effective pore-size distribution available to the other fluid. Thus the degree of saturation of a given phase has pronounced effects on the observed level of dispersion. More recently, Delshad *et al.*⁵³ confirm the dependence of multiphase dispersion on saturations.

As Section 4.1 mentions, most mathematical models of species transport in multiphase systems ignore hydrodynamic dispersion. There are, however, at least three noteworthy exceptions. The first is the compositional model developed by Young¹⁶⁴, who assumes the secondorder tensor form

$$\mathbf{D}_{\alpha} = (D_{\alpha,\mathrm{mol}} + \alpha_{\alpha,t} | \mathbf{v}^{\alpha} |) \mathbf{1} + (\alpha_{\alpha,t} - \alpha_{\alpha,t}) \frac{\mathbf{v}^{\alpha} \mathbf{v}^{\alpha}}{|\mathbf{v}^{\alpha}|}$$

for each fluid phase α . Here $D_{\alpha,mol}$ stands for the molecular diffusion coefficient in phase α , and $\alpha_{\alpha,t}$ and $\alpha_{\alpha,t}$ signify the longitudinal and transverse dispersivities, respectively, in phase α . This formulation amounts to a natural extension of the standard hydrodynamic dispersion model to multiphase flows. A model described by Abriola¹ and Abriola and Pinder² assumes a related form for dispersion within a phase, namely

$$\mathbf{D}_{\alpha} = \mathbf{D}_{\alpha, \text{mol}} + \mathbf{D}_{1} : \mathbf{v}^{\alpha} \mathbf{v}^{\alpha}$$

where $\mathbf{D}_{\alpha,\text{mol}}$ is a second-order tensor adcounting for the effects of molecular diffusion in phase α , modified by the matrix tortuosity, and \mathbf{D}_1 is a fourth-order tensor. This form extends the tensor equation proposed by Bear²³ on theoretical grounds. Finally, Baehr and Corapcioglu²⁰ and Corapcioglu and Baehr⁴⁹ derive a set of flow equations for immiscible contaminant transport incorporating a dispersion tensor for each phase; however, they do not postulate a precise tensorial form for dispersion.

Multiphase hydrodynamic dispersion appears to be one area of uncertainty where numerical simulation cannot shed much light. The fundamental questions that plague modelers are the same ones that arise in singlephase flows. What is the mathematical form of dispersion? How can we measure it? Do scale dependencies and asymmetric effects influence dispersion? It seems apparent that these questions address themselves primarily to experimentalists, guided ideally by theoretical studies of continuum mixtures such as that advanced by Bowen³¹.

5.3 Multiphase contaminant flows

In recent years interest has arisen in multiphase flows involving immiscible groundwater contaminants. It has long been common practice to store or dispose of hazardous chemicals in near-surface or underground sites, and fluids escaping from these sites pose serious threats to groundwater supplies. Many hazardous chemicals and wastes take the form of nonaqueous-phase liquids, or NAPL. Common examples include gasoline, polychlorinated biphenyls (PCB), chlorinated hydrocarbons, coal tars and creosotes¹⁵⁴. However, many dumpsites harbour a menagerie of chemical wastes, making it difficult to characterize the NAPL chemically. The multiphase flows that lead to contamination of groundwater are physically quite complex, and, despite the pressing need for predictive tools, numerical simulation of NAPL flows remains in its infancy.

One type of flow that is important in this context is the simultaneous flow of NAPL and water in the unsaturated zone. This soil layer usually lies between near-surface NAPL sources and the water table and therefore acts as the main pathway for groundwater contamination. As we illustrated in Section 3.1, the flow of a single liquid in the unsaturated zone already poses a difficult nonlinear problem, so one might expect that multiliquid flows will be even harder to simulate numerically.

Current efforts in multiphase unsaturated flows focus mainly on developing physical understanding. Schwille¹³⁵, for example, discusses the migration of immiscible organics in the unsaturated zone, reviewing such fundamental processes as capillary action, volatilization of the organic species, and microbial degradation. Allen⁹ applies continuum mixture theory to develop a set of flow equations for two liquids in the unsaturated zone. By analysing a medium containing air (A), NAPL (N) and water (W), he derives a pair of partial differential equations, each resembling Richards' equation in form:

$$\left(C_{\alpha} + \frac{\Theta_{\alpha}S_{s,\alpha}}{\phi}\right)\frac{\partial\psi_{a}}{\partial t} = \nabla \cdot \left[k_{r\alpha}\mathbf{K} \cdot (\nabla\psi_{\alpha} + \nabla Z)\right] \qquad (25)$$

for $\alpha = N$ or W. Several variables appearing in this equation are analogous to those appearing in the singleliquid case: C_{α} is the specific moisture capacity of phase α ; Θ_{α} is the moisture content of α ; ψ_{α} is the pressure head in phase α ; **K** is the soil's hydraulic conductivity and Z is depth below some datum. Also appearing are the variables $S_{s,\alpha}$, which is the specific storage associated with phase α , and $k_{r\alpha}$, signifying the relative permeability of the soil matrix to phase α . The pair of flow equations given by equation (25) constitutes a nonlinear system. Coupling between the equations occurs through the dependence of Θ_{α} , $S_{s,\alpha}$ and $k_{r\alpha}$ on the pressure heads ψ_{α} ; the capillarity relationships $\psi_{\alpha} = \psi_{\alpha}(\Theta_N, \Theta_W)$, and the restriction $\Theta_N + \Theta_W = \phi(1 - S_A)$.

In what appears to be the first effort at numerically simulating multiphase unsaturated flows, Faust⁶⁹ develops a two-dimensional finite-difference model for the flow of water and NAPL. This model uses a two-equation formulation similar to that given by equation (25). To solve the discretized flow equations, Faust devises a fully implicit scheme akin to the SS method used in black-oil simulation. As with other models of multiphase flows, Faust's simulator uses upstream-weighted relative permeabilities to accommodate possible hyperbolic behaviour, as explained in Section 4.2.

As a practical matter, the simultaneous flow of NAPL and water is only part of the multiphase contamination problem. Groundwater contamination itself occurs because of mass transfer between NAPL and water. Even though NAPL may be immiscible with water, some of its constituent species may dissolve in water at very small concentrations. While highly dilute, the resulting solution of organics in water is often toxic or carcinogenic. Therefore, a complete mathematical description of multiphase contaminant flows ought to incorporate phaseexchange effects more familiar in the setting of compositional reservoir simulators.

Very little work has been done in this area. Baehr and Corapcioglu²⁰ propose a model consisting of individual flow equations for each species. Since their model aims principally at predicting pollution from gasoline spills, they include in their formulation such effects as microbial degradation, equilibrium partitioning among fluid phases, and adsorption onto the solid phase. Abriola¹ and Abriola and Pinder^{2,3} present a finite-difference model of species transport in an air-water-NAPL system. This simulator accommodates interphase mass transfer through the use of equilibrium ratios analogous to those discussed in Section 4.3. The model solves the nonlinear algebraic equations resulting from the finite difference approximation using a scheme patterned after the SS method reviewed in Section 4.2. Considering the range of problems solved and the analyses given of the code's performance, this is perhaps the best documented model of multiphase, multispecies contaminant transport appearing in the literature at this writing.

6. OUTSTANDING PROBLEMS: NUMERICS

Quite a few of the difficulties arising in numerical simulation of multiphase flows concern the limitations of the numerical methods themselves. Here the problem is that the numerical techniques in common use produce approximations that are in some way unrealistic based on our understanding of the flows that they model. In this case the challenge to researchers is to devise new methods or to modify existing approaches to permit more accurate simulations. We shall examine three types of numerical difficulties of topical interest: grid orientation effects, front tracking and local grid refinement.

6.1 Grid-orientation effects

Since the early 1970s, petroleum engineers have recognized that many discrete methods for solving fluid flow equations give qualitatively different results when one changes the orientation of the spatial grid with respect to the geometry of the physical flow. Todd, O'Dell and Hirasaki¹⁴⁹ first reported this phenomenon in a simulator of immiscible flow. They noted that the effects of grid orientation are especially pronounced at large mobility ratios. A severe example occurs in steamflood simulation⁴⁴, where solutions generated using different grid orientations apparently converge to different answers. Since these investigations, a substantial body of research has developed in the effort to overcome or mitigate gridorientation effects in reservoir simulators.

One of the first effective techniques for reducing gridorientation effects appeared in 1979, when Yanosik and

McCracken¹⁶² presented a nine-point finite-difference scheme that reduces grid-orientation effects for square grids. The nine-point scheme approximates derivatives at a point (x_i, y_i) in two-dimensional domains by using values at all adjacent nodes instead of the corner nodes only. Thus the nine-point analog of the Laplacian on a uniform grid is

$$\nabla^2 u|_{i,j} = \frac{1}{6\Delta x^2} \left[4(u_{i+1,j} + u_{i-1,j} + u_{i,j+1} + u_{i,j-1}) + (u_{i+1,j-1} + u_{i-1,j-1} + u_{i-1,j+1} + u_{i+1,j-1}) - 20u_{i,j} \right]$$

Coats and Ramesh⁴⁶ observe that the nine-point formulation exhibits poor behaviour when used on nonuniform spatial grids. Bertiger and Padmanabhan²⁵ explain this poor performance by demonstrating that the usual ninepoint formulation on nonuniform grids yields an inconsistent approximation to ∇^2 . These authors then propose a modified nine-point scheme that restores consistency while still reducing the grid-orientation effect. In another approach, Potempa¹²³ advances a finite-element technique that is closely related to the Yanosik-McCracken nine-point difference scheme but again preserves consistency. Several other investigators have devised modified finite-difference schemes yielding solutions that are largely independent of grid-orientation effects; among them are Vinsome and Au¹⁵⁵; Frauenthal, di Franco and Towler⁷⁰; Shubin and Bell¹⁴² and Preuss and Bödvarsson¹²⁵.

Finite-element techniques also admit variants that reduce grid-orientation effects. Among the more promising groups of finite-element schemes in this regard are mixed methods^{50,67,10}. The motivation behind these techniques is to compute accurate Darcy velocities explicitly rather than incurring the loss of accuracy associated with standard schemes requiring the differentiation of fluid pressures. Thus, for example, we factor the second-order pressure equation

$$\nabla \cdot (k \nabla p) = 0$$

into two first-order equations

$$\mathbf{v} = -k\nabla p$$
$$-\nabla \cdot \mathbf{v} = 0$$

By properly choosing the trial functions for v and p, we can compute pressures and velocities having the same order of accuracy. In problems involving the effects of species transport the mixed method is especially effective when used in conjunction with time-stepping procedures based on modified methods of characteristics⁶⁷. A variety of numerical experiments reported in the references cited above demonstrate the method's ability to give good numerical results even in problems with highly variable material properties.

6.2 Front-tracking methods

As we have seen in previous sections, several multiphase flows in porous media exhibit sharp fronts that can be modelled as discontinuous fluid interfaces. The saltwater toe and the Buckley–Leverett saturation shock are two examples of such discontinuities. Discrete approximations using fixed finite elements or finitedifference cells have difficulty in capturing the behaviour of these sharp fronts, since the computational procedures tend to smear information over the spatial subregions of the discretizations. Front-tracking methods aim at circumventing this difficulty by assigning computational degrees of freedom to the unknown location of the front. Solving for the frontal locations along with the variables characterizing the smooth parts of the flow allows the modeller to track the front explicitly without introducing numerical diffusion. Since one can concentrate many degrees of freedom at the interface, front tracking methods also hold great promise in the simulation of viscous fingering.

Front-tracking methods have their roots in numerical applications of the method of characteristics in convection-dominated flows. The first applications of this approach in porous-media simulation addressed the miscible transport of solutes in single-phase flows^{73,120}. In the method of characteristics, one replaces a partial differential equation by a system of ordinary differential equation agrees with the chain rule. For example, by comparing the Buckley–Leverett saturation equation

$$\frac{\partial S_W}{\partial t} + \frac{qf'_W(S_W)}{\phi} = 0 \tag{26}$$

with the chain rule

$$\frac{\mathrm{d}t}{\mathrm{d}\xi}\frac{\partial S_W}{\partial t} + \frac{\mathrm{d}x}{\mathrm{d}\xi}\frac{\partial S_W}{\partial x} = \frac{\mathrm{d}S_W}{\mathrm{d}\xi}$$

one can see that $dS_W/d\xi = 0$ along curves $\xi(x, t)$ in the (x, t)-plane where $dx/dt = qf'_W(S_W)/\phi$. Loci of constant S_W therefore travel with speed $qf'_W(S_W)/\phi$. This fact allows us to compute the position of the constant-saturation shock as it moves across a one-dimensional domain.

Perhaps the most extensively applied front-tracking scheme in the current literature is that of Glimm and his coworkers^{77,79,93}. This approach uses an IMPES formulation for two-dimensional immiscible displacements in the absence of capillarity. The scheme solves the pressure equation on a finite-element grid whose element boundaries move to align themselves with the saturation shock. To update saturations, the scheme uses standard interior methods in regions where the saturation is smooth and couples to the smooth solution a Riemann problem propagating the interface. This frontal propagation relies on a method of characteristics akin to the one-dimensional version outlined above, taking advantage of a local coordinate system aligned with the shock to advance the discontinuity in its normal direction. Thus the actual computations required to track the front reduce one-dimensional ordinary differential to locally equations.

Jensen and Finlayson^{85,86} introduce an alternative scheme for front-tracking that gives good results in convection-dominated species-transport problems. This method defines a set of moving coordinates based on the method of characteristics for the hyperbolic, or purely convective, part of the partial differential equations. Within this moving coordinate system, the convectiondominated transport problem reduces to a problem of the diffusion type. Jensen and Finlayson construct a finiteelement grid attached to the moving coordinates, ensuring that the grid in the vicinity of the sharp front is sufficiently fine to avoid the occurrence of nonphysical oscillations in the numerical solution.

In a third approach to front tracking, the Mathematics Group at the Lawrence Berkeley Laboratory applies the theory of Riemann problems for first-order hyperbolic systems to solve the immiscible flow equations using the random choice method^{47,48,4}. The random choice method, developed as a numerical technique by Chorin⁴⁰, is an effective procedure for approximating nonlinear hyperbolic conservation laws such as equation (26). The method replaces the unknown function $S_W(x, t)$ by a piecewise constant approximation $\hat{S}_{W}(x,t)$ and then solves a sequence of Riemann problems, each advancing the numerical solution by sampling the piecewise constant function \hat{S} to determine initial data. When the solution possesses shocks, the random choice method preserves their sharp fronts, since the sampling at each time step avoids the introduction of spurious intermediate values in the numerical solution. However, the method allows small errors in the shock location since the sampling identifies the frontal position only to within the resolution limits imposed by the spatial grid. Although developed for onedimensional flows, the random choice method admits extensions to two-dimensional problems. Colella, Concus and Sethian⁴⁷ describe the use of operator splitting techniques to decompose a two-dimensional equation into a sequence of one-dimensional equations.

6.3 Adapative local grid refinement

Many problems involving multiphase flows in porous media exhibit behaviour whose structure is localized in small subregions of the spatial domain. We have already encountered such phenomena in the form of wetting fronts and saturation shocks. Similar localized behaviour occurs near wellbores or in the moving concentration fronts found in convection-dominated species transport processes. To capture the essential physics of these features often requires a spatial grid capable of providing high resolution in their vicinity. Grid refinement is especially important in view of the common use of loworder upstream-weighted approximations in nearhyperbolic flows. As frequently applied, these approximations introduce a numerical diffusion error whose magnitude is $\mathcal{O}(\Delta x)$ for grids of mesh Δx . By refining the spatial grid in the vicinity of the front, one reduces numerical diffusion by shrinking Δx , all the while preserving the desirable effects of upstream weighting.

Generating this extra resolution usually poses few difficulties if the locus of highly structured behaviour remains constant in time. However, in the case of moving fronts, for example, the zones where increased resolution is needed move through the spatial domain as time progresses. Under these circumstances the refined portion of the grid must be capable of moving in time to follow the localized structure of the solution. Such schemes fall under the rubric of *adaptive local grid refinement* (ALGR). While ALGR schemes are generally difficult to implement, the technical literature in this area is vast. Therefore the review that follows merely highlights results that appear relevant in multiphase flow simulation.

There are three basic approaches to ALGR. One of these is to increase the polynomial degree of the approximation to the solution in regions needing refinement. Such techniques are called *p-methods*. Another approach is to add computational degrees of freedom in the regions of refinement, keeping the polynomial degree of the approximation constant. These techniques are perhaps most appropriate when used in conjunction with upstream weighting, since they reduce numerical diffusion by shrinking Δx . Such methods are called *h*-methods. Finally, there are several techniques that allow the location of the spatial nodes in the grid to act as variables in the numerical approximation. By solving for the nodal locations and nodal solution values simultaneously, one effectively forces the grid to move in time to accommodate the structure of the solution. These methods are called *moving finite element* (MFE) techniques.

Reports of underground flow simulators using pmethods are not very numerous. Chase³⁷ describes a chemical flood simulator based on a finite-element Galerkin method that employs hybrid trial functions. These trial functions use C^0 piecewise bilinear Lagrange functions in smooth regions of the flow but insert C^1 piecewise bicubic Hermite functions in the vicinity of steep gradients. Mohsen¹⁰⁰ describes another p-method applied in finite-element collocation solutions of the Buckely-Leverett equation. This approach refines a coarse grid consisting of C^1 piecewise cubic Hermite functions by substituting C^1 piecewise quintic functions near the saturation shock.

The use of h-methods has been more popular. One reason for this fact may be a general aversion to the oscillatory tendencies associated with polynomial approximations of high degree. Another reason is undoubtedly that h-methods fit more naturally into the framework of finite-difference approximations, which do not explicitly use trial functions. Quite a few ALGR schemes for finite differences have appeared; among them are the methods of von Rosenberg¹⁵⁷, Heinemann and van Handelmann⁸¹ and Douglas *et al.*⁵⁷, who present both finite-difference and finite-element schemes. A considerable amount of theoretical work and numerical experimentation has focused on finite-element schemes with $ALGR^{19,52,24,54}$. One of the problems that arises in the construction of adaptive refinement codes is the management of the data defining the grid as its structure changes. There are great computational advantages associated with the invention of data structures that can accommodate the dynamic refinement and unrefinement of a grid without destroying the efficiency of matrix solution algorithms²¹.

MFE methods adopt a somewhat different approach^{35,98,74,55}. For an equation of the form $\partial u/\partial t$ – $\mathcal{A}u=0$, where \mathcal{A} is a spatial differential operator, we begin with a piecewise polynomial trial function \hat{u} having unknown time-dependent coefficients $u_1(t), \ldots, u_N(t)$. In addition, we allow the coordinates of the spatial nodes $\bar{\mathbf{x}}_1, \dots, \bar{\mathbf{x}}_N$ to be variable. By choosing $\{\partial u_i/\partial t, \bar{\mathbf{x}}_i\}_{i=1}^N$ to minimize $\|\partial \hat{u}/\partial t - \mathcal{A}\hat{u}\|_2$ in a Galerkin sense, one can develop a finite-element approximation in which the nodes tend to concentrate around regions where the solution exhibits localized structure. To prevent all of the nodes from accumulating near shocks, however, one must impose certain penalties on the clustering of nodes. A variety of internodal spring functions and viscosity-like devices exist to help preserve good global approximations by maintaining adequate separation between nodes.

ALGR techniques have a wide range of potential applications in general computational mechanics. Fluid flows in particular exhibit highly localized behaviours for

which local refinement is an attractive alternative to globally fine grids. Gas dynamic shocks, hydraulic jumps, moving interfaces, and such singularities as sources, sinks and corners are just a few examples of these features.

7. CONCLUSIONS

Throughout this review we have seen several facets of multiphase flows in porous media reappear in various applications. These physical and computational peculiarities emerge as major themes in the numerical simulation of flows. Let us close by recapitulating these themes.

Every flow we have examined obeys a nonlinear, timedependent partial differential equation. Nonlinearity is a characteristic feature of multiphase porous-media flows, owing to the fact that the permeability of the rock matrix to one fluid varies with the saturation of any other fluid. Further nonlinearities can arise when storage or compressibility effects imply pronounced dependence on pressure in the accumulation terms or when there is strong coupling within a system of flow equations. The nonlinear governing differential equations generally give rise to nonlinear algebraic equations in the approximating discretizations. These algebraic systems, in turn, demand iterative solution, and therefore one commonly finds Newton-Raphson schemes or related procedures imbedded in implicit time-stepping methods for these problems.

Another common feature in multiphase porous-media flows is the occurrence of sharp fronts or moving boundaries in the fluid system. The Buckley–Leverett saturation shock stands as a classic example. Similar interfaces arise in other contexts: unsaturated flows can give rise to wetting fronts, and the saltwater intrusion problem exhibits a moving boundary in the toe of the saltwater wedge. Sharp fronts pose difficulties to the numerical analyst, since they require high spatial resolution to model and are sometimes associated with uniqueness issues. In certain classes of flows they can also exhibit instability, as when viscous fingering occurs in displacements at adverse mobility ratios. The most natural solutions to these sharp-front difficulties are fronttracking methods and adaptive local grid refinement.

Finally, various numerical aspects of modelling multiphase flows combine to require truly large-scale computations. A typical simulator solves large, sparse matrix equations at every iteration of every time step. When compositional effects are present, the code must solve nonlinear thermodynamic constraints as well. The desirability of local grid enrichment, front-tracking algorithms, or moving grid schemes adds to this scale of calculation both in complexity and in computational effort. Scientists who model multiphase underground flows have every reason to applaud the emerging generation of supercomputers and parallel architectures, since these machines may spell the difference between compromise in the approximation of complex flows and the practical achievement of realistic simulations.

ACKNOWLEDGEMENTS

The Wyoming Water Research Center supported much of this work through a grant to study multiphase contaminant flows. The National Science Foundation provided support through grant number CEE-8404266. This paper was presented at the NATO Advanced Study Institute on Fundamentals of Transport Phenomena in Porous Media, 14–23 July, 1985, Newark, Delaware, USA.

REFERENCES

- 1 Abriola, L. M. Multiphase Migration of Organic Compounds in a Porous Medium, Springer-Verlag, Berlin, 1984
- 2 Abriola, L. M. and Pinder, G. F. A multiphase approach to the modelling of porous media contamination by organic compounds 1. Equation development, *Water Resources Research*, 1985, **21**, 11-18
- 3 Abriola, L. M. and Pinder, G. F. A multiphase approach to the modelling of porous media contamination by organic compounds 2. Numerical simulation, *Water Resources Research*, 1985, **21**, 19–26
- 4 Albright, N. and Concus, P. On calculating flows with sharp fronts in a porous medium, *Fluid Mechanics in Energy Con*servation, J. D. Buckmaster, ed., Society for Industrial and Applied Mathematics, Philadelphia, Pa., 1980, 172–184
- 5 Allen, M. B. How upstream collocation works, International Journal for Numerical Methods in Engineering, 1983, 19, 1753– 1763
- 6 Allen, M. B. A collocation model of compositional oil reservoir flows, *Mathematical Methods in Energy Research*, K. I. Gross, ed., Society for Industrial and Applied Mathematics, Philadelphia, Pa., 1984, 157–180
- 7 Allen, M. B., Collocation Techniques for Compositional Flows in Oil Reservoirs, S'ringer-Verlag, Berlin, 1984
- 8 Allen, M. B., Why upwinding is reasonable, Finite Elements in Water Resources, J. P. Laible et al., eds, Springer-Verlag, Berlin, 1984, 13–23
- 9 Allen, M. B. Mechanics of multiphase fluid flows in variably saturated porous media, *International Journal for Engineering Science*, 1985, to appear
- 10 Allen, M. B., Ewing, R. E. and Koebbe, J. V. Mixed finite-element methods for computing groundwater velocities, *Numerical Methods for Partial Differential Equations*, 1985, to appear
- 11 Allen, M. B. and Murphy, C. A finite-element collocation method for variably saturated flows in porous media, *Numerical Methods* for Partial Differential Equations, to appear
- 12 Allen, M. B. and Pinder, G. F. Collocation simulation of multiphase porous-medium flow, *Society of Petroleum Engineers Journal*, 1983, 135–142
- 13 Allen, M. B. and Pinder, G. F. The convergence of upstream collocation in the Buckley-Leverett problem, Society of Petroleum Engineers Journal, 1985, to appear
- 14 Amaefule, J. O. and Handy, L. L. The effect of interfacial tensions on relative oil/water permeabilities of consolidated porous media. Society of Petroleum Engineers Journal, 1982, 371-381
- media, Society of Petroleum Engineers Journal, 1982, 371-381
 Appleyard, J. R., Cheshire, I. M. and Pollard, R. K. Special techniques for fully-implicit simulators, *Third European Symposoium on Enhanced Oil Recovery*, F. J. Fayers, ed., Elsevier Scientific Publishing Co., Amsterdam, 1981, 395-408
- 16 Aronson, D. G. Nonlinear diffusion problems, Free Boundary Prlblems: Theory and Applications, Fasano, A. and Primicerio, M. (eds), Vol. 1, Pitman Advanced Publishing Program, Boston, Mass., 1983, 135–149
- 17 Atkin, R. J. and Craine, R. E. Continuum theories of mixtures: Basic theory and historical development, *Quarterly Journal of Applied Mathematics*, 1976, **29**(2), 209–244
- 18 Aziz, K. and Settari, A. Petroleum Reservoir Simulation, Applied Science Publishers, London, 1979
- 19 Babuska, I. and Rheinboldt, W. C. Error estimates for adaptive finite element computations, Society for Industrial and Applied Mathematics Journal of Numerical Analysis, 1978, 15, 736-754
- 20 Baehr, A. and Corapcioglu, M. Y. A predictive model for pollution from gasoline in soils and groundwater, *Proceedings*, Petroleum Hydrocarbons and Organic Chemicals in Groundwater: Prevention, Detection and Restoration, Houston, Texas, 1984
- 21 Bank, R. E. and Sherman, A. H. A refinement algorithm and dynamic data structure for finite element meshes, *Center for Numerical Analysis Technical Report 166*, University of Texas, Austin, Texas, 1980
- 22 Bardon, C. and Longeron, D. G. Influence of interfacial tensions on relative permeability, *Society of Petroleum Engineers Journal*, 1980, 391–401

- 23 Bear, J. On the tensor form of dispersion in porous media, Journal of Geophysical Research, 1961, 66, 1185–1197
- 24 Beiterman, M. A posteriori error estimation and adaptive finite element grids for parabolic equations, Adaptive Computational Methods for Partial Differential Equations, Babuska, I. et al. (eds), Society for Industrial and Applied Mathematics, Pniladelphia, Pa., 1983, 123–141
- 25 Bertiger, W. I. and Padmanabhan, L. Finite difference solutions to grid orientation problems using IMPES, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1983, 163–172
- 26 Birkkoff, G. Numerical fluid dynamics, Society for Industrial and Applied Mathematics Review, 1983, 25, 1–34
- 27 Björdammen, J. B. and Coats, K. H. Comparison of alternating direction and successive overrelaxation techniques in simulation of reservoir fluid flow, Society of Petroleum Engineers Journal, 1969, 47-58
- 28 Blair, P. M. and Weinaug, C. F. Solution of two-phase flow problems using implicit finite differences, *Society of Petroleum Engineers Journal*, 1969, 417–424
- 29 Bowen, R. M. Incompressible porous media models by the use of the theory of mixtures, *International Journal of Engineering Science*, 1980, 18, 1129–1148
- 30 Bowen, R. M. Compressible porous media models by the use of the theory of mixtures, *International Journal of Engineering Science*, 1982, 20, 697–735
- 31 Bowen, R. M. Diffusion models implied by the theory of mixtures, Appendix 5A to *Rational Thermodynamics*, 2nd ed., by C. A. Truesdell, Springer-Verlag, New York, NY, 1984, 237–263
- 32 Breitenbach, E. A., Thurnau, D. H. and van Poolen, H. K. Solution of the immiscible fluid flow simulation equation, *Society* of Petroleum Engineers Journal, 1969, 155–169
- 33 Bresler, E. Simultaneous transport of solutes and water under transient unsaturated flow conditions, *Water Resources Re*search, 1973, 9, 975–986
- 34 Buckley, S. E. and Leverett, M. C. Mechanism of fluid displacement in sands, *Transactions*, American Institute of Mining, Metallurgical and Petroleum Engineers, 1942, 146, 107–116
- 35 Carey, G. F., Mueller, A., Sephehrnoori, K. and Thrasher, R. L. Moving elements for reservoir transport processes, *Proceedings*, Fifth Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1979, 135–144
- 36 Celia, M. A. and Pinder, G. F. An analysis of alternatingdirection methods for parabolic equations, *Numerical Methods* for Partial Differential Equations, 1985, 1, 57–70
- 37 Chase, C. A. Variational simulation with numerical decoupling and local mesh refinement, *Proceedings*, Fifth Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1979, 73– 94
- 38 Chien, M. C. H., Lee, S. T. and Chen, W. H. A new fully implicit compositional simulator, *Proceedings*, Eighth Symposium on Reservoir Simulation, Society of Petroleum Engineers, Feb., 1985, 7–30
- 39 Chorin, A. J. and Marsden, J. E. A Mathematical Introduction to Fluid Mechanics, Springer-Verlag, New York, NY, 1979, Chapter 3
- 40 Chorin, A. J. Random choice solution of hyperbolic systems, Journal of Computational Physics, 1976, 22, 517-533
- 41 Chuoke, R. L., van Meurs, P. and van der Poel, C. The instability of slow, immiscible, liquid-liquid displacements in permeable media, Society of Petroleum Engineers Journal, 1959, 188–194
- 42 Coats, K. An equation-of-state compositional model, Society of Petroleum Engineers Journal, 1980, 363–376
- 43 Coats, K. Reservoir simulation: State of the art, Journal of Petroleum Technology, 1982, 1633-1642
- Coats, K. H., George, W. D., Chu, C. and Marcum, B. E. Threedimensional simulation of steamflooding, presented at the Sept. 30–Oct. 3, 1973, Annual Fall Technical Conference and Exhibition of the Society of Petroleum Engineers
- 45 Coats, K. H., Nielsen, R. L., Terhune, M. H. and Weber, A. G. Simulation of three-dimensional, two-phase flow in oil and gas reservoirs, Society of Petroleum Engineers Journal, 1967, 377–388
- 46 Coats, K. H. and Ramesh, A. B. Effect of grid type and difference scheme on pattern steamflood results, presented at the Sept. 26– 29, 1982, Fall Technical Conference and Exhibition of the Society of Petroleum Engineers
- 47 Colella, P., Concus, P. and Sethian, J. Some numerical methods for discontinuous flows in porous media, *The Mathematics of Reservoir Simulation*, Ewing, R. E. (ed.), Society for Industrial and Applied Mathematics, Philadelphia, Pa., 1983, 161–186

- Concus, P. Calculation of shocks in oil reservoir modeling and porous flow, *Numerical Methods for Fluid Dynamics*, Morton, K. W. and Baines, M. J. (eds), Academic Press, New York, NY, 1982, 165–178
- 49 Corapicoglu, M. Y. and Baehr, A. Immiscible contaminant transport in soils and groundwater with an emphasis on petroleum hydrocarbons: System of differential equations vs. single cell model, *Water Sciences and Technology*, 1985, to appear
- 50 Darlow, B. L., Ewing, R. E. and Wheeler, M. F. Mixed finite element methods for miscible displacement problems in porous media, *Proceedings*, Sixth Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1982, 137–146
- 51 Davis, H. T. and Scriven, L. E. The origins of low interfacial tensions for enhanced oil recovery, presented at the September 21–24, 1980, Annual Fall Technical Conference and Exhibition of the Society of Petroleum Engineers of AIME
- 52 Davis, S. and Flaherty, J. An adaptive finite element method for initial-boundary value problems for partial differential equations, Society for Industrial and Applied Mathematics Journal for Scientific and Statistical Computing, 1983, **3**, 6–27
- 53 Delshad, M., MacAllister, D. J., Pope, G. A. and Rouse, B. A. Multiphase dispersion and relative permeability experiments, presented at the Sept., 1982, Society of Petroleum Engineers Annual Fall Technical Conference and Exhibition, held in New Orleans, La
- 54 Diaz, J. C., Ewing, R. E., Jones, R. W., McDonald, A. E., Uhler, L. M. and von Rosenberg, D. U. Self adaptive local grid refinement in enhanced oil recovery, *Proceedings*, Fifth International Symposium on Finite Elements and Flow Problems, Austin, Texas, Jan. 23–26, 1984, 479–484.
- 55 Djomehri, M. J. and Miller, K. A moving finite element code for general systems of partial differential equations in two dimensions, University of California Center for Pure and Applied Mathematics Report PAM-57, Berkeley, Calif., Oct. 1981
- 56 Douglas, J. Jr., Alternating direction methods for three space variables, Numerische Mathematik, 1962, 2, 91–98
- 57 Douglas, J. Jr., Darlow, B. L., Wheeler, M. F. and Kendall, R. P. Self-adaptive finite element and finite difference methods for onedimensional two-phase immiscible flow, *Computer Methods in Applied Mechanics and Engineering*, 1984, 47, 119–130
- 58 Douglas, J. Jr. and Dupont, T. A finite-element collocation method for quasilinear parabolic equations, *Mathematics of Computation*, 27, 17–28
- 59 Douglas, J. Jr., Peaceman, D. W. and Rachford, H. H. Jr. A method for calculating multidimensional immiscible displacement, *Transactions*, American Institute of Mining, Metallurgical and Petroleum Engineers, 1959, **216**, 297–306
- 60 Douglas, J. Jr. and Rachford, H. H. Jr. On the numerical solution of heat conduction problems in two and three space variables, *Transactions*, American Mathematical Society, 1956, **82**, 421–439
- 61 Eringen, A. C. and Ingram, J. D. A continuum theory of chemically reacting media—I, *International Journal of Engineer*ing Science, 1965, 3, 197–212
- 62 Ewing, R. E. Alternating-direction Galerkin methods for parabolic, hyperbolic and Sobolev partial differential equations, *Proceedings of the Special Year in Numerical Analysis*, University of Maryland, College Park, Md., 1981, 123–150
- 63 Ewing, R. E. and George, J. H. Viscous fingering in hydrocarbon recovery processes, *Mathematical Methods in Energy Research*, Gross, K. I. (ed.), Society for Industrial and Applied Mathematics, Philadelphia, Pa., 1984, 194–213
- 64 Ewing, R. E. and Heinemann, R. F. Incorporation of mixed finite element methods in compositional simulation for reduction of numerical dispersion, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, Nov., 1983, 341–347
- 65 Ewing, R. E. and Heinemann, R. F. Mixed finite element approximation of phase velocities in compositional reservoir simulation, *Computer Methods in Applied Mechanics and Engineering*, 1984, **47**, 161–176
- 66 Ewing, R. E., Russell, T. F. and Wheeler, M. F. Simulation of miscible displacement using mixed methods and a modified method of characteristics, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1983, 71– 82
- 67 Ewing, R. E., Russell, T. F. and Wheeler, M. F. Convergence analysis of an approximation of miscible displacement in porous media by mixed finite elements and a modified method of characteristics, *Computer Methods in Applied Mechanics and Engineering*, 1984, **47**, 73–92

Adv. Water Resources, 1985, Volume 8, December 183

- 68 Fatt, I. and Dykstra, H. Relative permeability studies, *Transactions*, American Institute of Mining, Metallurgical and Petroleum Engineers, 1951, **192**, 249–256
- 69 Faust, C. R. Transport of immiscible fluids within and below the unsaturated zone: A numerical model, *Water Resources Research*, 1985, 21, 587–596
- 70 Frauenthal, J. C., di Franco, R. B. and Towler, B. F. Reduction of grid orientation effects in reservoir simulation using generalized upstream weighting, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1983, 7–16
- 71 Fried, J. J. Groundwater Pollution, Elsevier Scientific Publishing Co., Amsterdam, 1975
- 72 Fussell, L. T. and Fussell, D. D. An iterative technique for compositional reservoir models, *Society of Petroleum Engineers Journal*, 1979, 211–220
- 73 Garder, A. O., Peaceman, D. W. and Pozzi, A. L. Numerical calculation of multidimensional miscible displacement by the method of characteristics, *Society of Petroleum Engineers Jour*nal, 1964, 26–36
- 74 Gelinas, R. J., Doss, S. K. and Miller, K. The moving finite element method: Applications to general partial differential equations with large multiple gradients, *Journal of Computational Physics*, 1981, 40, 202–221
- 75 Gibbs, J. W. On the equilibrium of heterogeneous substances, *Transactions*, Connecticut Academy, 1876, 3, 108–248, and 1878, 343–524
- 76 Glimm, J., Isaacson, E. L., Lindquist, B., McBryan, O. and Yaniv, S. Statistical fluid dynamics: The influence of geometry on surface instabilities, *The Mathematics of Reservoir Simulation*, Ewing, R. E. (ed.), Society for Industrial and Applied Mathematics, Philadelphia, Pa., 1983, 137–160
- 77 Glimm, J., Lindquist, B., McBryan, O. and Padmanabhan, L. A front tracking reservoir simulator, five-spot validation studies and the water coning problem, *The Mathematics of Reservoir Simulation*, Ewing, R. E. (ed.), Society for Industrial and Applied Mathematics, Philadelphia, Pa., 1983, 107–135
- 78 Glimm, J., Marchesin, D. and McBryan, O. Unstable fingers in two-phase flow, Communications in Pure and Applied Mathematics, 1981, 34, 53-75
- 79 Glimm, J., Marchesin, D. and McBryan, O. A numerical method for two phase flows with an unstable interface, *Journal of Computational Physics*, 1981, 39, 91–119
- 80 Heinemann, R. F. Simulation of compositional oil recovery processes, *Mathematical Methods in Energy Research*, Gross, K. I. (ed.), Society for Industrial and Applied Mathematics, Philadelphia, Pa., 1984, 214–235
- 81 Heinemann, Z. E. and von Hantelmann, G. Using local grid refinement in a multiple application reservoir simulator, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1983, 205–218
- 82 Hoa, N. T., Gaudu, R. and Thirriot, C. Influence of the hysteresis effect on transient flows in saturated-unsaturated porous media, *Water Resources Research*, 1977, 13, 992–996
- 83 Huyakorn, P. S. and Pinder, G. F. A new finite element technique for the solution of two-phase flow through porous media, *Advances in Water Resources*, 1978, 1, 285–298
- 84 Huyakorn, P. S. and Pinder, G. F. Computational Methods in Subsurface Flow, Academic Press, New York, NY, 1983
- 85 Jensen, O. K. and Finlayson, B. A. A solution of the transport equation using a moving coordinate system, Advances in Water Resources, 1980, 3, 9–18
- 86 Jensen, O. K. and Finlayson, B. A. A numerical technique for tracking sharp fronts in studies of tertiary oil recovery pilots, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1983, 61–70
- 87 Jerrauld, G. R., Davis, H. T. and Scriven, L. E. Frontal structure and stability in immiscible displacement, *Proceedings*, Fourth Symposium on Enhanced Oil Recovery, Society of Petroleum Engineers and US Department of Energy, 1984, 2, 135–144
- 88 Kazemi, H., Vestal, C. R. and Shank, G. D. An efficient multicomponent numerical simulator, Society of Petroleum Engineers Journal, 1978, 355–368
- 89 Koval, E. J. A method for predicting the performance of unsteady miscible displacement, Society of Petroleum Engineers, 11963, 145–154
- 90 Lax, P. D. Hyperbolic systems of conservation laws II, Communications in Pure and Applied Mathematics, 1957, 10, 537– 566
- 91 Leverett, M. C. Capillary behaviour in porous solids, Transac-

tions, American Institute of Mining, Metallurgical and Petroleum Engineers, 1941, 142, 159-169

- 92 Leverett, M. C. and Lewis, W. B. Steady flow of gas-oil-water mixtures through unconsolidated sands, *Transactions*, American Institute of Mining, Metallurgical and Petroleum Engineers, 1941, **142**, 107–120
- 93 McBryan, O. Shock tracking methods in 2-D flows, Ninth National Applied Mechanics Congress, Cornell University, Ithaca, NY, 1982
- 94 McLean, J. W. The fingering problem in flow through porous media, thesis presented to the California Institute of Technology, at Pasadena, Cal., in 1980 in partial fulfillment of the requirements for the degree of Doctor of Philosophy
- 95 Meijerink, J. A. and Van der Vorst, H. A. An iterative solution method for linear systems of which the coefficient matrix is a symmetric *M*-matrix, *Mathematics of Computation*, 1977, 31, 148-162
- 96 Mercer, J. W. and Faust, C. R. The application of finite element techniques to immiscible flow in porous media, *Finite Elements in Water Resources*, Gray, W. G. et al. (eds), London, Pentech Press, 1977, 21–43
- 97 Mercer, J. W. Larson, S. P. and Faust, C. R. Simulation of saltwater interface motion, *Ground Water*, 1980, **18**, 374–385
- 98 Miller, K. and Miller, R. N. Continuously deforming finite elements, I, Society for Industrial and Applied Mathematics Journal of Numerical Analysis, 1981, 18, 1019–1032
- 99 Milly, P. C. D. A mass-conservative procedure for time-stepping in models of unsaturated flow, *Finite Elements in Water Re*sources, Laible, J. P. et al. (eds), Springer-Verlag, London, 1984, 103-112
- 100 Mohsen, M. F. N. Numerical experiments using 'adaptive' finite elements with collocation, *Finite Elements in Water Resources*, Laible, J. P. et al. (eds), Springer-Verlag, Berlin, 1984, 45–61
- 101 Molina, N. M. A systematic approach to the relative permeability problem in reservoir simulation, presented at the September 21– 24, 1980, Annual Fall Technical Conference and Exhibition of the Society of Petroleum Engineers of AIME
- 102 Morel-Seytoux, H. J. Introduction to flow of immiscible liquids in porous media, *Flow Through Porous Media*, De Weist, R. J. M. (ed.), Academic Press, New York, NY, 1969, 456–516
- 103 Morrow, N. R. Physics and thermodynamics of capillary action in porous media, Symposium on Flow Through Porous Media, Nunge, R. (ed.), American Chemical Society Publications, Washington, DC, 1969, 83-108
- 104 Muskat, M., Wykoff, R. D., Botset, H. G. and Meres, M. W. Flow of gas-liquid mixtures through sands, *Transactions*, American Institute of Mining, Metallurgical and Petroleum Engineers, 1937, **123**, 69–96
- 105 Nakano, Y. Application of recent results in functional analysis to the problem of wetting fronts, *Water Resources Research*, 1980, 16, 314–318
- 106 Narasimhan, T. N. and Witherspoon, P. A. Numerical model for saturated-unsaturated flow in deformable porous media 3. Applications, *Water Resources Research*, 1978, 14, 1017–1033
- 107 Neumann, S. P. Saturated-unsaturated seepage by finite elements, Journal of the Hydraulics Division of ASCE, 1073, 99, 2233–2251
- 108 Ngheim, L. X., Fong, D. K. and Aziz, K. Compositional Modelling with an equation of state, *Society of Petroleum Engineers Journal*, 1981, 687–698
- 109 Nolen, J. S. Numerical simulation of compositional phenomena in petroleum reservoirs, *Proceedings*, Third Symposium on Reservoir Simulation, Society of Petroleum Engineers, Jan., 1973, 269–284
- 110 Northrup, E. J. and Woo, P. T. Application of preconditioned conjugate-gradient-like methods in reservoir simulation, *Proceedings, Eighth Symposium on Reservoir Simulation*, Society of Petroleum Engineers, Feb., 1985, 375–386
- 111 Oleinik, O. A. Uniqueness and stability of the generalized solution to the Cauchy problem for a quasi-linear equation, *American Mathematical Society Translations*, Series 2, 1973, 33, 285–290
- 112 Passman, S. L., Nunziato, J. W. and Walsh, E. K. A theory of multiphase mixtures, Appendix 5C to *Rational Thermodynamics*, 2nd ed., by C. A. Truesdell, Springer-Verlag, New York, NY, 1984, 286–325
- 113 Peaceman, D. W. Numerical solution of the nonlinear equations for two-phase flow through porous media, *Nonlinear Partial Differential Equations: A Symposium on Methods of Solution*,

Ames, W. F. (ed.), Academic Press, New York, NY, 1967, 171–191 114 Peaceman, D. W. Fundamentals of Numerical Reservoir

- Simulation, Elsevier Scientific Publishing Co., Amsterdam, 1977
 Peaceman, D. W. and Rachford, H. H. Jr. The numerical solution of parabolic and elliptic differential equations, Journal of the Society for Industrial and Applied Mathematics, 1955, 3, 28-41
- Peletier, L. A. The porous medium equation, Applications of Nonlinear Analysis in the Physical Sciences, Amann, H. et al. (eds), Pitman Advanced Publishing Program, Boston, Mass., 1981, 229-240
- 117 Peng, D.-Y. and Robinson, D. R. A new two-constant equation of stage, Industrial and Engineering Chemistry: Fundamentals, 1976, 15, 53-64
- 118 Peters, E. J. and Flock, D. L. The onset of instability during twophase immiscible displacement in porous media, *Society of Petroleum Engineers Journal*, 1981, 249–258
- 119 Philip, J. R. Numerical solution of equations of the diffusion type with diffusivity concentration dependent. II, *Australian Journal* of *Physics*, 1957, **10**, 29-40
- 120 Pinder, G. F. and Cooper, H. H. Jr. A numerical technique for calculating the transient position of the saltwater front, *Water Resources Research*, 1970, **6**, 875–882
- 121 Pinder, G. F. and Page, R. F. Finite element simulation of salt water intrusion on the South Fork of Long Island, *Finite Elements in Water Resources*, Gray, W. G. *et al.* (eds), Pentech Press, Plymouth, UK, 1977, 2.51–2.69
- 122 Ponting, D. K., Foster, B. A., Naccache, P. F., Nichols, M. O., Pollard, R. K., Rae, J., Banks, D. and Walsh, S. K. An efficient fully implicit simulator, *Society of Petroleum Engineers Journal*, 1983, 544–552
- 123 Potempa, T. Finite element methods for convection dominated transport problems, thesis presented to Rice University, at Houston, Texas, in 1982 in partial fulfillment of the requirements for the degree of Doctor of Philosophy
- 124 Prévost, J. H. Mechanics of continuous porous media, International Journal of Engineering Science, 18, 787-800
- 125 Preuss, K. and Bödvarsson, G. S. A seven-point finite difference method for improved grid orientation in pattern steamfloods, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, 1983, 175–184
- 126 Raats, P. A. C. Applications of the theory of mixtures in soil physics, Appendix 5D to *Rational Thermodynamics*, 2nd ed., by C. A. Truesdell, Springer-Verlag, New York, NY, 1984, 326–343
- 127 Reeves, M. and Duguid, J. O. Water movement through saturated-unsaturated porous media: A finite-element Galerkin model, Oak Ridge National Laboratories Report 4927, Oak Ridge, Tenn., 1975
- 128 Richards, L. A. Capillary conduction of liquids in porous media, *Physics*, 1931, 1, 318–333
- 129 Risnes, R., Dalen, V. and Jensen, J. I. Phase equilibrium calculations in the near-critical region, *Proceedings*, Third European Symposium on Enhanced Oil Recovery, Fayers, F. J. (ed.), Elsevier Scientific Publishing Co., Amsterdam, 1981, 329– 350
- 130 Roebuck, I. F., Henderson, G. E., Douglas, J. and Ford, W. T. The compositional reservoir simulator: Case I—The linear model, Society of Petroleum Engineers Journal, 1969, 115–130
- 131 Sá da Costa, A. A. G. and Wilson, J. L. Coastal seawater intrusion: A moving boundary problem, *Finite Elements in Water Resources*, Wang, S. Y. *et al.* (eds), University of Mississippi, Oxford, Miss., 1980, 2.209–2.218
- 132 Saffman, P. G. and Taylor, G. I. The penetration of a fluid into a porous medium or Hele-Shaw cell containing a more viscous liquid, *Proceedings of the Royal Society of London* A, 1958, 245, 312–329
- 133 Scheidegger, A. E. *The Physics of Flow Through Porous Media*, 3rd ed., University of Toronto Press, Toronto, 1974
- 134 Schiegg, H. O. Experimental contribution to the dynamic capillary fringe, *Symposium on Hydrodynamic Diffusion and Dispersion in Porous Media*, Pavia-Italia, Rome, 1977
- 135 Schwille, F. Migration of organic fluids immiscible with water in the unsaturated zone, *Pollutants in Porous Media*, Yaron, B., Dagan, G. and Goldshmid, J. (eds), Springer-Verlag, Berlin, 1984, 27–49
- 136 Segol, G. A three-dimensional Galerkin-finite element model for the analysis of contaminant transport in saturated-unsaturated porous media, *Finite Elements in Water Resources*, Gray, W. G. *et al.* (eds), Pentech Press, London, 1977, 2.123–2.144
- 137 Settari, A. and Aziz, K. Treatment of the nonlinear terms in the numerical solution of partial differential equations for multi-

phase flow in porous media, International Journal of Multiphase Flow, 1975, 1, 817–844

- 138 Settari, A., Price, H. S. and Dupont, T. Development and application of variational methods for simulation of miscible displacement in porous media, *Society of Petroleum Engineers Journal*, 1977, 228–246
- 139 Shamir, V. and Dagan, G. Motion of the seawater interface in a coastal aquifer: A numerical solution, *Water Resources Research*, 1971, 7, 644–647
- 140 Shapiro, A. M. and Pinder, G. F. Solution of immiscible displacement in porous media using the collocation finite element method, *Finite Elements in Water Resources*, Holz, K. P. et al. (eds), Springer-Verlag, Berlin, 1982, 9.61–9.70
- 141 Sheldon, J. W., Zondek, B. and Cardwell, W. T. Onedimensional, incompressible, non-capillary two-phase flow in a porous medium, *Transactions*, American Onstitute of Mining, Metallurgical and Petroleum Engineers, 1959, **216**, 290–296
- 142 Shubin, G. R. and Bell, J. B. An analysis of the grid orientation effect in numerical simulation of miscible displacement, *Computer Methods in Applied Mechanics and Engineering*, 1984, 47, 47-72
- 143 Stone, H. L. Iterative solution of implicit approximations of multidimensional partial differential equations, Society for Industrial and Applied Mathematics Journal of Numerical Analysis, 1968, 5, 530-568
- 144 Stone, H. L. Estimation of three-phase relative permeability and residual oil data, *Journal of Canadian Petroleum Technology*, 1973, **12** (4), 53–61
- 145 Stone, H. L. and Garder, A. O. Jr. Analysis of gas-cap or dissolved-gas reservoirs. *Transactions*, American Institute of Mining, Metallurgical and Petroleum Engineers, 1961, 222, 92– 104
- 146 Taylor, G. I. Dispersion of soluble matter in solvent flowing slowly through a tube, *Proceedings*, Royal Society of London, Series A, 1953, 219, 186–203
- 147 Thomas, G. H., Countryman, G. R. and Fatt, I. Miscible displacement in a multiphase system, *Society of Petroleum Engineers Journal*, 1963, 189–196
- 148 Todd, M. R. and Longstaff, W. J. The development, testing and application of a numerical simulator for predicting miscible flood performance, *Journal of Petroleum Technology*, 1972, 874–882
- 149 Todd, M. R., O'Dell, P. M. and Hirasaki, G. J. Methods for increased accuracy in numerical reservoir simulators, Society of Petroleum Engineers Journal, 1972, 515–530
- 150 Towler, B. F. and Killough, J. E. Comparison of preconditioners for the conjugate gradient method in reservoir simulation, *Proceedings*, Sixth Symposium on Reservoir Simulation, Society of Petroleum Engineers, Feb., 1982, 7–14
- 151 van Genuchten, M. Th. A comparison of numerical solutions of the one-dimensional unsaturated-saturated flow and mass transport equations, Advances in Water Resources, 1982, 5, 47–55
- 152 van Genuchten, M. Th. An Hermitian finite element solution of the two-dimensional saturated-unsaturated flow equation, *Advances in Water Resources*, 1983, **6**, 106–111
- 153 Van Quy, N., Simandoux, P. and Corteville, J. A numerical study of diphasic multicomponent flow, Society of Petroleum Engineers Journal, 1972, 171–184
- 154 Villaume, J. F. Investigations at sites contaminated with dense, nonaqueous phase liquids (NAPLs), *Ground Water Monitoring Review*, Spring, 1985, 60–74
- 155 Vinsome, P. K. and Au, A. One approach to the grid orientation problem in reservoir simulation, presented at the Sept. 23–26, 1979, Annual Fall Technical Conference and Exhibition of the Society of Petroleum Engineers
- 156 von Neumann, J. First report on the numerical calculation of flow problems, *Collected Works*, Taub, A. H. (ed.), Vol. 5, The MacMillan Co., New York, NY, 1963, 664–712
- 157 von Rosenberg, D. U. Local mesh refinement for finite difference methods, presented at the Sept. 26–29, 1982, Fall Technical Conference and Exhibition of the Society of Petroleum Engineers
- 158 Watts, J. W. A compositional formulation of the pressure and saturation equations, *Proceedings*, Seventh Symposium on Reservoir Simulation, Society of Petroleum Engineers, Nov., 1983, 113–138
- 159 Welge, H. J. A simplified method for computing oil recovery by gas or water drive, *Transactions*, American Institute of Mining, Metallurgical and Petroleum Engineers, 1952, 195, 91–98
- 160 Wilson, D. C., Tan, T. C. and Casinader, P. C. Control of numerical dispersion in compositional simulation, *Third European Symposium on Enhanced Oil Recovery*, Fayers, F. J.

(ed.), Elsevier Scientific Publishing Co., Amsterdam, 1981, 425-440

- Wykoff, R. D. and Botset, H. G. The flow of gas-liquid mixtures 161 through unconsolidated sands, *Physics*, 1936, 7, 325–345 Yanosik, J. L. and McCracken, T. A. A nine point finite difference
- 162 simulator for realistic prediction of adverse mobility ratio displacements, Society of Petroleum Engineers Journal, 1979, 253-262
- 163 Yortsos, Y. C. and Huang, A. B. Linear stability of immiscible displacement including continuously changing mobility and capillary effects, Proceedings, Fourth Symposium on Enhanced Oil Recovery, Society of Petroleum Engineers and US Department of Energy, 1984, 2, 145-162
- 164 Young, L. C. A study of spatial approximations for simulating fluid displacements in petroleum reservoirs, Computer Methods in Applied Mechanics and Engineering, 1984, 47, 3-46
- 165 Young, L. C. and Stephenson, R. E. A generalized compositional approach for reservoir simulation, Society of Petroleum Engineers Journal, 1983, 727-742

NOMENCLATURE

Capital letters

- coefficient A
- [A]system matrix
- .A spatial operator
- formation volume factor; coefficient R
- B_{j} (see Table 1)
- Ċ specific moisture capacity; compressibility; coefficient
- D diffusion coefficient
- D hydrodynamic dispersion tensor
- H_0 Hermite cubic of the first kind
- H_1 Hermite cubic of the second kind
- number of nodes Ι
- Jtemporal domain
- K hydraulic conductivity scalar
- Κ hydraulic conductivity tensor
- K_{ij} (see Table 1)
- [K]stiffness matrix
- М mobility ratio
- M_{ij} (see Table 1)
- [M]mass matrix
- basis function; number of species Ν
- [N]SIP matrix
- order symbol 0
- Р number of phases
- Q_{ij} (see Table 1)
- Ñ residual
- R_s solution gas-oil ratio
- $\{R\}$ residual vector
- Ŕ spatial region
- S saturation
- S_s specific storage
- Т transmissibility (defined variously)
- Ζ depth below datum

Lower case letters

z-coordinate of confining layer а b z-coordinate of interface; derivative of 1/B

Adv. Water Resources, 1985, Volume 8, December

- b body force
- z-coordinate of free surface С
- unit vector e

186

- fractional flow; fugacity
- $\{f\}$ boundary data vector gravitational acceleration
- h hydraulic head
- $\{h\}$ vector of hydraulic heads

diffusive flux

j

k

k,

k

l

r

t

t

u

u

- permeability scalar
- relative permeability
- permeability tensor
- vertical thickness
- m momentum exchange rate
 - pressure
- $\{p\}$ vector of pressures flux; flow rate
- q flow rate vector q

 - mass exchange rate
- $\{r\}$ right-hand side vector specific yield
- S_{v} time
 - stress tensor
 - unknown function
 - diffusion velocity vector
- v velocity vector
- horizontal space coordinate х
- x spatial position vector
- vector of unknowns у
- \overline{z} vertical space coordinate
- Capital greek letters
- time-difference operator Δ_t
- Δt time increment
- Δx space increment
- Θ moisture content
- Λ mobility scalar
- ۸ mobility tensor
- Σ interface
- Υ compositional flux coefficients
- Φ free surface
- Ω spatial domain

Lower case greek letters

- dispersity α
- gravity coefficient γ
- δ iterative increment operator
- ξ curve in (x, t)-plane
- λ flux coefficient
- dynamic viscosity μ
- ρ density
- ϕ volume fraction; porosity
- test function φ
- ψ pressure head
- mass fraction ω

Subscripts and superscripts

gas species

longitudinal

molecular

time level

oil phase

oil species

rock phase

iteration level

node indices; species indices

collocation point index

nonaqueous liquid phase

- A air
- atm atmospheric
- С capillary
- F freshwater
- G gas phase

g

k

1

т

Ν

n

0

0

R

mol

i, j

RC reservoir conditions ref reference saltwater S STC stock-tank conditions total Т transverse t Wwater phase water species w z-direction Ζ

phase index α ∂

boundary

*

Special symbols average; collocation point approximation derivative; dummy variable

dimensionless; upstream; preconditioner